

RES 20-1808(9-77)

LAND CORNER RECORD

SKAMANIA

County

Corner Code No.

J-1


T. 5 N, R. 5 E, W.M.

Segregated Surveys:

Name: W.C. #1 TO N.W. COR 18

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.



1 History of Corner Establishment and Subsequent Restoration:

ORIGINALLY SET BY GLO. SURVEY JULY 6, 1897

CORNER REMONUMENTED 1966 BY BLM WITH NEW BT'S

(ACTUAL CORNER INFO ABOVE)

2 Description of Evidence Found:

POSSIBLE GLO BT WITH VISIBLE SCRIBE ALSO HAS BLM TAG WHICH READS: DISTANCE-104 LKS, DIRECTION-UNLEDGIRLE

BLM BT - 14" HEMLOCK, N 64° W, 64 LINKS, FACE GROWN OVER CORNER GAUDD POST IN WASHOUT, STEEL POST ON N. EDGE WASHOUT ORIGINAL BT. IN WASHOUT

(ACTUAL CORNER INFO ABOVE)

3 Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 151-K Page No. 21 Date of work 9-4-81

SET 2 1/2" x 30" PIPE
24" IN GROUND WITH SMALL
MOUND OF STONES AROUND
AND BRASS CAP MARKED

T 5 N
W C
R 4 E R 5 E
S 12 S 7
S 13 S 18
V
1981
LS 15652

3" HEMLOCK
SCRIBED X BT

N 61° E
39.21'
N 61° E
39.21'

MEASUREMENTS TAKEN HORIZ FROM BRASS
SURVEY TAG NAILED IN TOP OF NEWLY SCRIBED
BS TO CENTER ON MON.
BT'S HAVE 6" RED BAND PAINTED AROUND THEM
AND 54-4 & 54-3 SIGNS

00-09-00" E, 40°

ACTUAL CORNER, NOT SET, FALLS
IN WASHOUT

Washington Plane Coordinates:

Zone, Y

X

Order Accuracy. Derived From:

Pin Pointed on Photo No.

Date

Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
50, Laws of 1973. Date September 23, 1981

Signature

Michael M. Hobbs

Certificate No.

LS 15652

93128

AUDITOR'S CERTIFICATE

Filed for record this 28 day of Sept 1981 at 11:30 A.M. In
Book 5/5 of Monumental at page 3 at the request of

James Associates, Michael M. Hobbs

Paul Messenger
County Auditor