


93486

BOOK 4/7 PAGE 8

RES 20-1808(9-77)

LAND CORNER RECORD

T. 4 N. R. 7E W.M. Skamania County
 Segregated Surveys: Corner Code No. R-17
 Name: Section Corner Corner No.:
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.



1. History of Corner Establishment and Subsequent Restoration:

Corner established in July or Aug. 1895 by Deputy Jacob Richardson under his contract No. 457.

Marked orig. 4" Maple post.

36" Fir N41E, 89 lks..

36" Fir S20E, 77 lks..

30" Fir S66W, 179 lks..

36" Fir N67W, 64 lks..

2. Description of Evidence Found:

U.S.F.S. 2" Brass cap on 2" Iron pipe 1" above ground. 3/4" Iron pipe S45E, 3 ft. accepted FS Brass cap.

Orig. 36" now 48" rotted D-Fir stump no marks remaining, N67W, 42.2 ft. to face.

Orig. 36" now 40" rotted D-Fir stump N41E, 58.7 ft. to face, no marks remaining.

Orig. 36" now 48" rotted D-Fir stump S20E, 51.0 ft. to face, scribing BT visible.

Bearing Tree in Sec. 27 possible windfall-does not fit for bearing.

Remark by Olsen 9" D-Fir N15E, 5.11 ft to R/R spike in bottom of 4 blazes.

Fence South and West.

See Wind River Experimental Forest Timber Survey Report-1933 corner listed as set from original evidence.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 3. Page No. 3. Date of work Oct. 1981.

Set guard post West with sign 54-4 and BM 102 decal.

Mailed 54-4 and BT signs to all BT's and painted band and blazes red.

New Bearing Trees:

8" D-Fir N67E, 8.0 ft. scribed T4NR7ES23 upper blaze and a lower blaze scribed

BT and with a 3/4" Brass disk stamped PLS 16337.

10" D-Fir S25E, 12.8 ft. scribed T4NR7ES26 upper blaze and a lower blaze scribed

BT and with a 3/4" Brass disk stamped PLS 16337.

18" D-Fir S76W, 61.0 ft. scribed T4NR7ES27 upper blaze and a lower blaze scribed

BT and with a 3/4" Brass disk stamped PLS 16337.

11" D-Fir N46W, 36.9 ft. scribed T4NR7ES22 upper blaze and a lower blaze scribed

BT and with a 3/4" Brass disk stamped PLS 16337.

Washington Plane Coordinates: Zone Y, X
 Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 11/15/81

Signature Larry D. Bishop

Certificate No. 16337

[SEAL]



AUDITOR'S CERTIFICATE

Filed for record this 18th day of December 1981 at 9:10 A.M. In Book 4/7 of Monuments at page 8 at the request of Larry D. Bishop

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.