

LAND CORNER RECORD

T. 4 N. R. 7E. W.M. Skamania County
Segregated Surveys: Corner Code No. T-17
Name: One-quarter corner Corner No.:
DEC. HES. Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.



1. History of Corner Establishment and Subsequent Restoration:

Corner established in July or Aug. 1895 by Deputy Jacob Richardson under his contract No. 457.

Marked orig. 4" Yew post.
36" Cedar N40E 5 lks..
6" Hemlock N52W 15 lks..

2. Description of Evidence Found:

No evidence of the original corner or its accessories found during a thorough search of the area indicated by proportion and creek calls.

3/4" Iron pipe set by Olson PLS 9025.
3/4" Iron pipe S40W, 3.1 ft. from Olson pipe.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

Page No. 4 Date of work Oct. 1981

Set 2"x30" Gal. steel pipe with a 2" Brass cap in place of Olson Marked:
Iron pipe-buried Olson pipe next to monument set. T4N R7E
Set guard post South with sign 54-4 only. X
Nailed 54-4 and BT signs to BT's and painted S27 S26
band and blazes red. 1981
New Bearing Trees: PLS 16337

20" D-Fir S70E, 18.4 ft. scribed S26 upper
blaze and a lower blaze scribed BT and with
a 3/4" Brass disk stamped PLS 16337.
12" Alder S16W, 14.5 ft. bark scribed S27 BT
and with a 3/4" Brass disk stamped PLS 16337.

Washington Plane Coordinates: Zone, Y X
Order Accuracy. Derived From:
Pin Pointed on Photo No. Date. Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 11/18/81

Signature: [Signature] Certificate No. 16337

Registered
Ind. Dir. S
X



AUDITOR'S CERTIFICATE

Filed for record this 18th day of December 1981 at 9:25 A.M. In Book 4/7 of Monuments at page 12 at the request of Bishop Surveying Co.

J. M. Allen
County Auditor