

LAND CORNER RECORD

T. 4 N. R. 7E W.M. Skamania County
Segregated Surveys: Corner Code No. L-9

Name: One-quarter corner Corner No.:
P.L.C. Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459, in July/Aug. 1895.

Set Yew post

Scribed 10" Fir N65W-25 lks.

6" Fir S60E-36 lks.

2. Description of Evidence Found:

No evidence of the original corner or its accessories found—cruisers mark N on an 18" D-Fir and two small Fir with 4 notches facing each other @ N45E/S45W 2 ft. apart N70W of corner set—35'.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5. Page No. 13 Date of work 4/82

Set 2"x30" Aluminum pipe with a 2" Aluminum cap. Marked:

New Bearing Trees:

10" D-Fir S42W, 4.3 ft. scribed 1312 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 1633.

14" D-Fir S40E, 4.3 ft. scribed 1815 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 1633.

Set guard post South with sign 34-4 only.

Nailed BT and 34-4 signs to BT's and painted band and blazes red.

Washington Plane Coordinates: Zone Y X
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at:

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me, or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 4/82

Signature

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 19th day of May 1982 at 10:00 A.M. in Book 10 of 100 at page 1 at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973