

LAND CORNER RECORD

T. 4 N, R. 7E, W.M. Skamania County
Segregated Surveys: Corner Code No. G-13
Name: One-quarter corner Corner No.
D.C. H.S. Tract Mining Claim, Indian Allotment, Federal Reserve Township.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.
Set post
Scribed 18" Fir N50E-26 lks..
6" Maple N40W-13 lks..

2. Description of Evidence Found:

No evidence of the original corner or BT's found during a thorough search of the area indicated. Corner set at proportion position.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 31 Date of work 5/82

Set 2 1/2"x30" Gal steel pipe with a 2 1/2" Brass cap in a mound of stone. Marked:

New Bearing Trees:

9" D-Fir N45E, 41.1 ft. scribed 4510 upper blaze
and a lower blaze scribed BT and with a 3/4"

Brass disk stamped PLS 16337.

18" Hemlock S24W, 25.6 ft. scribed 459 upper blaze
and a lower blaze scribed BT and with a 3/4"

Brass disk stamped PLS 16337.

Set guard post west with sign 54-4 and BM 102 decal.

Nailed 54-4 and BT signs to BT's and painted bark and blazes red.

T. 4N, R. 7E

S9 | S10

1982

PLS 16337

Washington Plane Coordinates: Zone Y X
Order Accuracy. Derived From:

Pin Pointed on Photo Nos. Date. Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5/12/82

Signature

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 310 day of June 1982 at P.O. M. In
Book of 100 volumes at page 1 at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

LAND CORNER RECORD

T. 4 N. R. 7E W.M. Skamania County
Segregated Surveys: Corner Code No. G-43

Name: One-quarter corner Corner No.:
DLC, HSS, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.

Set post

Scribed 18" Fir N50E-26 lks..

6" Maple N70W-18 lks..

2. Description of Evidence Found:

No evidence of the original corner or BT's found during a thorough search of the area indicated. Corner set at proportion position.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 21 Date of work 5/82

Set 2 1/2"x30" Gal steel pipe with a 2" Brass cap in a mound of stone. Marked:

New Bearing Trees:

9" D-Fir N45E, 11.1 ft. scribed S80 upper blaze
and a lower blaze scribed BT and with a 3/4"

Brass disk stamped PLS 16337.

18" Hemlock S27W, 25.6 ft. scribed S89 upper blaze
and a lower blaze scribed BT and with a 3/4"

Brass disk stamped PLS 16337.

Set guard post west with sign 54-4 and BM 102 decal.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.

T. 4N R. 7E

S9 S10

1982

PLS 16337

Washington Plane Coordinates: Zone Y X
Order Accuracy Derived From

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5/82

Signature

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this day of June 1982 at P.M. In Book of 1800-1809 at page 224 at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.