

94126
RES 20-1808(9-77)

LAND CORNER RECORD

T. 4 N. R. 7E W.M. Skamania County
Segregated Surveys: Corner Code No. L-9
Name: One-quarter corner Corner No.:
B.L.C. R.R. Tract, Mining Claim, Indian Allotment, Federal Reserve Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.
Set Vew post
Scribed 10" Fir N65W-25 lks..
6" Fir S60E-36 lks..

2. Description of Evidence Found:

No evidence of the original corner or its accessories found - cruizers mark N on an 18" D-Fir and two small Fir with 4 notches facing each other N45E/S45W 1/2 ft. apart N70W of corner set-35'.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 13 Date of work 4/82

Set 2"x30" Aluminum pipe with a 2"x Aluminum cap. Marked:

New Bearing Trees:

10" D-Fir S42W, 4.9 ft. scribed S17 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

14" D-Fir S40E, 4.3 ft. scribed S16 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard post South with sign 54-4 only.

Nailed BT and 54-4 signs to BT's and painted band and blazes red.

Washington Plane Coordinates:

Zone Y

X

Order Accuracy: Derived From:

Pin Pointed on Photo No.

Date

Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 4/11/82

Signature

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 2nd day of June 1982 at 12:00 P.M. In Book of LAND SURVEYS at page 21 at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.