

LAND CORNER RECORD

Skamania County
T 4 N. R. 7E W.M. Corner Code No. E-11
Segregated Surveys:
Name: One-quarter corner Corner No.
D.L.C., H.P.S., Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:
Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.
Set post
Scribed 10" Alder S50W-22 lks..
8" Alder N68W-43 lks..

2. Description of Evidence Found:
No evidence of the orig. corner or its accessories found.
Set on line at index distance West of Section corner.
U.S. Fish and Wildlife Service monument bears N37-26-26E-45.13 ft..

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 14 Date of work 5/82

Set 2"x30" Aluminum pipe with a 2" Aluminum cap in a mound of stone. Marked:

New Bearing Trees:

20" D-Fir N60E, 11.9 ft. scribed 10" upper blaze and a lower blaze scribed ET and with a 3/4" Brass disk stamped H.S. 16337.

10" Cedar 142, 25.1 ft. scribed 10" upper blaze and a lower blaze scribed ET and with a 3/4" Brass disk stamped H.S. 16337.

Set guard posts South and West with sign 54- and 55-102

decals. Nailed 54- and 55- signs to ET's and painted band and blazes red.

Washington Plane Coordinates: Zone Y X

Order Accuracy Derived From:

Pin Pointed on Photo No. Date Located at:

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5/21/82

Signature

Certificate No. 16337

AUDITOR'S CERTIFICATE

Filed for record this 10 day of July 1982 at 2 P.M. In Book 10 of 10 at page 1 at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.