

94151
RES 20-1808(9-77)

4/7 4432 (1)

LAND CORNER RECORD

T. N. R. W.M. County
Segregated Surveys: Corner Code No. 6-
Name: One-quarter corner Corner No.
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1925.

Set post
Scribed 12" Hemlock 3324-3/4 lks..
= 12" Hemlock 3302-10 lks..

2. Description of Evidence Found:

No evidence of the original corner or its accessories found.


3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 11 Date of work 5/2

Set 2"x30" Aluminum rod 12" Aluminum cap. Marked: 40' 1/2
New Bearing Tree:
12" D-Pin 3342, 12" D-Pin 3342, 12" D-Pin 3342, 12" D-Pin 3342
and a lower blade scribed 34 and with a 3/4"
Brass disk stamped 12 16337
12" D-Pin 3342, 12" D-Pin 3342, 12" D-Pin 3342, 12" D-Pin 3342
and a lower blade scribed 34 and with a 3/4"
Brass disk stamped 12 16337
Set guard post west with sign 54-- only.
Nailed 54-- and 33 signs to 12's and painted red
and blades red.

Washington Plane Coordinates: Zone, Y, X
Order Accuracy: Derived From
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5/20/82
Signature: [Signature] Certificate No. 12377



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of
County Auditor

Form prescribed by Bureau of Surveys pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973