

## LAND CORNER RECORD

T. 7 N. R. 6E W.M. Skamania County  
Segregated Surveys: Corner Code No. R-19  
Name: One-quarter Corner Corner No.:  
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

### 1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis  
D.W. Shelton in July 1899, & Oct.-Dec. 1900 under  
Contract No. 552.

Set Cedar post.

Scribed 6" Alder S57E-31 lks..

10" Fir N19W-26 lks..

Remonumented by Floyd A. Brooks,  
Cadastral Surveyor in Oct. & Nov.  
1961.

Set 2 1/2" Iron post with Brass cap.

Scribed 22" Fir N12E-37 lks..

16" Hemlock S52W-26 1/2 lks

### 2. Description of Evidence Found:

B.L.M. Brass cap on an Iron post.

Orig. 10" now 1 1/4" sawed Fir stump N10E, 26 lks., blaze grown over.

Brooks 22" now 24" sawed Fir stump N12E, 37 lks. scribing visible.

Brooks 16" now 24" Hemlock S52W, 26 1/2 lks. healed blaze.

### 3. Describe Monument Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 3 Date of work 6/82

#### New Bearing Trees:

16" Hemlock N41W, 28.0 ft. scribed S23  
upper blaze and a lower blaze scribed BT  
and with a 3/4" Brass disk stamped PLS 16337.

Nailed 54-4 and BT signs to all BT's and  
painted band and blaze red.

Set guard posts South and West with sign  
54-4 and BM 102 decal.



Washington Plane Coordinates: Zone Y X  
Order Accuracy. Derived From:  
Pin Pointed on Photo No. Date Located at

### SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or  
under my direction in compliance with the provisions of Chapter  
50, Laws of 1973. Date

Signature Larry D. Bishop 16337  
Certificate No.

[SEAL]



### AUDITOR'S CERTIFICATE

Filed for record this 7th day of JULY 1982 at 11:30 P.M. In  
Book 7/6 of MONUMENTS at page 3 at the request of  
BISHOP SURVEYING INC.

County Auditor