

## LAND CORNER RECORD

T. 7 N. R. 6E W.M. Skamania County  
Segregated Surveys. Corner Code No. 7-19  
Name: Witness Corner Corner No.  
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

### 1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Set post

Scribed 30" Fir S47E-44 lks..

12" Cottonwood N64W-49 lks..

### 2. Description of Evidence Found:

1/4 corner falls in Swift Reservoir - set witness corner West on Section line.

### 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. Date of work June 1973

Set 2x4x30" Aluminum pipe with a 3" Aluminum cap in a mound of stone. Marked:

New Bearing Trees:

11" D-Fir N66E, 12.4 ft. scribed "X" on a square blaze chest high and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

24" D-Fir N66E, 4.2 ft. scribed "X" on a square blaze chest high and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard post West with sign 54-4 and BM 102 decal.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.

T. 7N R. 6E

W.C.

S26

S35

1982

PLS 16337

Washington Plane Coordinates: Zone, Y

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

### SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature

16337  
Certificate No.

### AUDITOR'S CERTIFICATE

Filed for record this 7th day of JULY 1982 at 11:30 A.M. In Book 7/6 of PLATS & COPIES at page 4 at the request of

County Auditor