

94303

RES 20-1808(9-77)

DOI 7/6 PAGE 5

LAND CORNER RECORD

T. 7 N, R. 6E W.M. County
 Segregated Surveys: Corner Code No. V-19
 Name: Witness Corner Corner No. 5
 DLC, RES, Tract, Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Set post

Scribed 30" Fir S47E-44 lks..

12" Cottonwood N64W-49 lks..

2. Description of Evidence Found:

1/4 corner falls in Swift Reservoir-set witness corner North on N/S Section centerline.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 6 Date of work June 1982

Set 2"x30" Aluminum pipe 20" in ground with a 3"x3" Aluminum cap in a mound of stone.

New Bearing Trees:

8" D-Fir N38W, 55.2 ft. scribed "X" on a square blaze chest high and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

8" D-Fir N25W, 74.5 ft. scribed "X" on a square blaze chest high and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard post with sign 54-4 and BM 102 decal North.

Painted band and blaze red on BT's - nailed 54-4 and BT signs to BT's.

Washington Plane Coordinates: Zone, Y

Order Accuracy. Derived From:

Pin Pointed on Photo No.

Date

Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature

16337

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 7th day of JULY 1982 at 11:20 A.M. In Book 776 of RECORDS at page 5 at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.