

94395

RES 20-1808(9-77)

BOOK 7/6

PAGE 7

LAND CORNER RECORD

Skamania

County

T. 2 N. R. 6E. W.M.

Corner Code No. V-17

Segregated Surveys:

Name: Section Corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.

Set Fir post.

Set concrete post with Brass cap.

Scribed 12" Fir N54E-39 lks..

Scribed 20" Fir N9E-90 1/2 lks..

12" Fir S40E-29 1/2 lks..

4" Fir S65W-52 lks..

12" Fir N52W-36 lks..

2. Description of Evidence Found:

2 1/2" B.L.M. Brass cap on 4"x4" Concrete post.

Orig. 12" now 25" D-Fir stump N54E, 25.7 ft..

Orig. 12" now 30" D-Fir S40E, 19.5 ft. blaze grown over.

Orig. 4" now 21" D-Fir S65W, 34.3 ft. blaze grown over.

Orig. 12" now 36" D-Fir N52W, 23.8 ft. blaze grown over.

Brooks 20" Fir N9E-90 1/2 lks., blaze grown over.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

2. Page No. 2 Date of work 6/72

Set guard posts North and East with signs 54-4 and BX 102 decals.

Painted red band and blazes red on BT's

Nailed signs 54-4 and 102 signs on BT's.

Washington Plane Coordinates: Zone, Y

X

Order Accuracy: Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature

Certificate No. 15337

[SEAL]



AUDITOR'S CERTIFICATE

Filed for record this 7th day of JULY 1972 at 11:20 A.M. In Book 7/6 of 1808(9-77) at page 7 at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.