

LAND CORNER RECORD

Skamania

T. 7 N. R. 6E W.M.

County

Corner Code No. V-21

Segregated Surveys:

Name: Section Corner

Corner No.

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.
- This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.
- Set Willow post.
- Scribed 3 1/4" Cedar N40E-47 lks..
- 14" Alder S21 1/2 E-35 lks..
- 16" Alder S20 1/2 W-39 lks..
- 8" Alder N40W-24 lks..
- Set Concrete post with Brass cap.
- Scribed 10" Fir N14E-86 lks..
- 20" Fir S74 1/2 E-42 1/2 lks..
- 18" Alder S25 1/2 W-54 lks..
- 10" Fir N8 1/2 W-44 lks..

2. Description of Evidence Found:

- 2 1/2" Brass cap on 4"x4" Concrete post.
- 18" Hemlock N65W, 61.1 ft. blaze grown over. Unrecorded BT.
- 54" Cottonwood S88W, 50.9 ft. blaze grown over. Unrecorded BT.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram, corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2. Page No. 1. Date of work 6/82.

New Bearing Trees:

- 6" Alder N35E, 12.6 ft. bark scribed T7N47E329
BT and with a 3/4" Brass disk stamped PLS 16337.
- 6" Alder S41E, 12.6 ft. bark scribed T7N47E329
and with a 3/4" Brass disk stamped PLS 16337.

Set guard post West with sign 54-4 only.
Nailed 54-4 and BT signs to BT's and painted
band and blazes red.

Washington Plane Coordinates: Zone Y X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature

16337
Certificate No.

[SEAL]



AUDITOR'S CERTIFICATE

Filed for record this 7th day of July 1982 at 11:30 A.M. In Book 716 of RECORDS at page 8 at the request of

County Auditor