

94328

RES 20-1808(9-77)

BOOK 7/6 PAGE 9

LAND CORNER RECORD

T. 7 N. R. 6E W.M. Skamania County
 Segregated Surveys Corner Code No. 8-15
 Name: One-quarter Corner Corner No.
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552. Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.
 Set Fir post. Set Iron post with Brass cap.
 Scribed 14" Fir S65/E-6 lks.. Scribed 10" Hemlock N28/E-34 lks..
 8" Dogwood N17/W-18 lks.. 8" Hemlock S9W-32 lks..

2. Description of Evidence Found:

BLM 2 1/2" Iron post with 3" Brass cap.
 Orig. 14" now 20" D-Fir uprooted open blaze S65/E-6 lks..
 Brooks 10" now 14" Hemlock blaze grown over N28/E-34 lks..

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 3 Page No. 3 Date of work June 1982

New Bearing Tree:

12" Hemlock S84E, 11.5 ft. scribed 162° upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 1982.

Nailed 54-4 and BM signs to BT's.

Painted red band and blazes red.

Set guard post with open 54-4 and BM 1002 second line.



Washington Plane Coordinates: Zone Y X
 Order Accuracy: Derived From:
 Pin Pointed on Photo No. Date Located at:

SURVEYOR'S CERTIFICATE

[SEAL]

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature

16357
Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 13th day of JULY 1982 at P.M. In Book 7/6 of MONUMENTS at page 9 at the request of

RICHARD SURVIVANT, INC.

J.M. Olson
County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.