

94331

RES 20-1808(9-77)

7/6

PAGE 12

## LAND CORNER RECORD

Skamania

County

T. 7 N. R. 6E W.M.

Corner Code No. P-13

Segregated Surveys:

Name: One-quarter Corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

## 1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.

Set Cedar post.

Set Iron post with Brass cap.

Scribed 16" Fir N89E-12 lks..

Scribed 16" Fir N66E-44 lks..

12" Fir S653/4W-13 lks..

9" Hemlock S351/4W-32 1/2 lks

## 2. Description of Evidence Found:

BLM 2 1/2" Iron post with Brass cap.

Orig. 16" now 18" D-Fir snag N89E-12 lks. scribing visible on opened blaze.

Brooks 16" now 18" D-Fir N66E-44 lks. healed blaze.

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 13 Date of work June 1982

New Bearing Trees:

12" Hemlock N33W, 64.5 ft. scribed 1/821 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard post South with sign 54-4 and BM 102 decal.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.

Washington Plane Coordinates: Zone Y

X

Order Accuracy. Derived From:

Pin Pointed on Photo No.

Date

Located at

## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature

16337

Certificate No.

## AUDITOR'S CERTIFICATE

Filed for record this 13th day of JULY 1982 at 12:00 P.M. In Book 7/2 of RECORDS at page 132 at the request of

BUREAU OF SURVEYS AND MAPS

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.