

LAND CORNER RECORD

Skamania

County

T. 7 N, R. 5E, W.M.

Corner Code No. G-9

Segregated Surveys:

Name: One-quarter corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.

Set Wh. Fir post.

Set Iron post with Brass cap.

Scribed 30" Hemlock N183/4E-27 lks..

Scribed 8" Fir S56E-22 1/2 lks..

6" Wh. Fir N253/4W-16 lks..

12" Wh. Fir N24W-58 lks..

2. Description of Evidence Found:

BIM 2" Iron post with Brass cap.

Orig. 30" now 48" Hemlock stump N183/4E-27 lks. scribing visible on unhealed blaze. Brooks 8" Fir now 12" Noble Fir N56E-22 1/2 lks. scribing visible on partially healed blaze.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 3 Date of work June 1972

New Bearing Tree:

10" D-Fir N53W, 14.0 ft. scribed 3/8" upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped FLS 1633.

Set guard post South with sign 34-4 only.

Nailed 34-4 and BT signs to BT's and painted band and blazes red.

Washington Plane Coordinates: Zone, Y

X

Order Accuracy: Derived From:

Pin Pointed on Photo No.

Date

Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature

16337

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 13th day of JULY 1972 at 12:30 P.M. In Book 116 of RECORDS at page 18 at the request of

County Auditor