

94739

LAND CORNER RECORD

T. 7 N. R. 6E, W.M. Skamania County
 Segregated Surveys: Corner Code No. J-15
 Name: One-quarter corner Corner No.:
 DLC, RES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis
 D.W. Shelton in July 1899, & Oct.-Dec. 1900 under
 Contract No. 552.

Set Wh. Fir post.

Scribed 14" Cedar N26E-37 lks..

10" Cedar S28E-36 lks..

2. Description of Evidence Found:

Orig. 14" now 20" sawed Cedar stump N26E-37 lks.-face burned out.

Orig. BT in Sec. 15 buried by fire trail construction.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 6 Page No. 8 Date of work July 1982

Set 2 1/2" x 30" Aluminum pipe with a 2 1/2" Aluminum cap.

Marked:

New Bearing Trees:

7" Hemlock S9W, 13.9 ft. scribed 1/8" S15 upper blaze
 and a lower blaze scribed BT and with a 3/4" Brass
 disk stamped PLS 16337.

Set guard post West with sign 54-4 and BM 102 decal.

Nailed 54-4 and BT signs to BT's and painted band and blazes
 red.

T. 7N R. 6E

S10

1/4 S15

1982

PLS 16337

Washington Plane Coordinates: Zone, Y

Order Accuracy. Derived From:

Pin Pointed on Photo No.

Date

Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
 under my direction in compliance with the provisions of Chapter
 50, Laws of 1973. Date AUG. 4, 1982

Signature

16337
 Certificate No.

[SEAL]

AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept. 1982 at 1:30 P.M. In
 Book 7/6 of Monument at page 27 at the request of

Gary M. Olson

County Auditor