

94752

LAND CORNER RECORD

T. 7 N, R. 6E, W.M. Skamania County
 Segregated Surveys: Corner Code No. E-23
 Name: Witness Corner Corner No.
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct. Dec. 1900 under Contract No. 552.
 Set Sandstone 14x10x6 mkd. WC on North face.
 W.C. 7" Cedar N73E-17 lks..
 10" Cedar S14E-15 lks..

2. Description of Evidence Found:

Point falls on gravel bar 15 ft. from undisturbed ground-stone if here no doubt has moved-no Cedar trees or stumps remain.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. Page No. 16 Date of work Aug. 1982

W.C. is 352.84 ft. East of 1/4 corner.
 Set 2 1/2"x30" Aluminum pipe with a 2 1/2" Aluminum cap in a mound of stone. Marked:

New Bearing Trees:

13" Hemlock N71W, 5.2 ft. with a square blaze chest high scribed "X" and with a 3/4" Brass disk stamped PLS 16337.

24" Cedar S40E, 7.0 ft. with a square blaze chest high scribed "X" and with a 3/4" Brass disk stamped PLS 16337.

Set guard post West with sign 54-4 only.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.

T. 7N R. 6E

W.C.

S1

S12

1982

PLS 16337

Washington Plane Coordinates: Zone, Y, X
 Order Accuracy. Derived From:
 Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 8/27/82

Signature

16337

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept 1982 at 1:30 P.M. In Book 7/6 of Monument at page 30 at the request of

County Auditor