

94769

7/6 PAGE 57

LAND CORNER RECORD

T. 7A N, R. 6E, W.M. Skamania County
 Segregated Surveys: Corner Code No. 3-21
 Name: Section Corner: Corner No.:
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Nov. 1900 under contract No. 553. Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.
 Set Hemlock Post
 Scribed 1/2" Cedar #732-68 lks..
 20" " 315/E-48 lks..
 36" " 3173/4-62 lks..
 66" " N61 A-91 lks..

2. Description of Evidence Found:

Set 2 1/2" Iron Post with Brass Cap
 Orig. 1/2" now 20" Cedar #732-68 lks.. holed blaze
 Orig. 20" now 40" Cedar 315/E-48 lks.. - Opened blaze
 Orig. 36" now 50" Cedar stump 3173/4-62 lks.. (record 62 lks.) no marks remaining on rotted blaze.
 Orig. 66" now 0" Cedar N61 A-91 lks.. Scribing visible

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

Page No. 10 Date of work 10/12/82

Now Clearing Area:

10" Hemlock 311A-51.0 ft. scribed with upper blaze and a lower blaze scribed 31 and with a 3/4" brass disk stamped PLS 1835

Set guard posts South and West with sign 54-1 and 102 Decal
 Nailed 34-4 and 102 signs to 31's and painted wood and blazes red

Washington Plane Coordinates: Zone, Y X
 Order Accuracy. Derived From:
 Pin Pointed on Photo No. Date Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date July 22, 1982

Signature Larry D. Bishop Certificate No. 16337

AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept 1982 at 1:30 P. M. In Book 7-6 of Monuments at page 57 at the request of

Signature Larry D. Bishop
 County Auditor