

7/6 2262 58

94770

LAND CORNER RECORD

T. 7N, R. 6E, W.M. County
 Segregated Surveys: Corner Code No. L-21
 Name: One-quarter corner Corner No.:
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis
 D.W. Shelton in July 1899, and Oct.-Dec. 1900 under
 Contract No. 552.

Set Cedar post

Scribed 12" Cedar 341B-17 lks.

12" hemlock 160A-30 lks.

Re-monumented by Floyd A. Brooks
 Cadastral Surveyor in Oct. & Nov.
 1961.

Set 2 1/2" Iron Post with a Brass Cap

Scribed 6" W. Pine 82E-10 1/2 lks.

6" W. Pine 139A-46 lks.

2. Description of Evidence Found:

Set 2 1/2" iron post with a Brass Cap

Orig. 12" now 20" Cedar 9" high stump - scribing visible - 341B-17 lks.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

Page No. 10 Date of work July 22, 1982

New bounding trees:

10" hemlock 165.1 100.2 ft. scribed 3/4" upper blaze and a lower blaze
 scribed 3/4" and with a 3/4" Brass disk stamped FIS 16337.
 2" Noble Fir 533B 13.3 ft. scribed 1/2" upper blaze and a lower blaze
 scribed 1/2" and with a 3/4" Brass disk stamped FIS 16337.

Set guard post South with sign 54-4.

Nailed 54-4 and 31 signs to 165.1 and painted band and blades red.

Washington Plane Coordinates: Zone, Y X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
 under my direction in compliance with the provisions of Chapter
 50, Laws of 1973. Date JULY 22, 1982

Signature

Certificate No. 16337

AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept 1982 at 2 P. M. In
 Book 7/6 of Monuments at page 58 at the request of

Barry D. Bishop
 Gary M. Olson
 County Auditor