

LAND CORNER RECORD

T. 3. N. R. 8 East, W.M. Skamania County
 Segregated Surveys: Corner Code No. E-7
 Name: n/a Corner No.: n/a
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Originally set by G.L.O. surveyor, Robert A. Webster, in 1896.
 An iron pipe with stamped brass cap set by Skamania County Engineers.
 Corner is shown on surveys recorded in Book 1 pages 118, 260, and 261; and
 Book 2 page 21.

2. Description of Evidence Found:

18" Fir B.T. stump with visible scribe at N 65 E, 19.7 feet.
 15" Fir B.T. stump and log with visible scribe at S 77 E, 19.5 feet.
 Above described Skamania County iron pipe.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.22 Page No. 56 Date of work 11-18-82

Shown on D.N.R. Final Map #462.

See corner diagram on reverse side.

Washington Plane Coordinates: South Zone, Y 161,250.81 X 1,662,088.29
 3rd Order Accuracy. Derived From: 1975 Olson Eng. survey data at S.W.
 corner Sec. 5 (Recorded in Bk 1 page 54, Records of Skamania County)
 Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
 under my direction in compliance with the provisions of Chapter
 50, Laws of 1973. Date Sept. 29, 1983

Signature

11977
 Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this 6TH day of OCTOBER 1983 at 1:00 P.M. In
 Book 3/8 of MONUMENTS at page 56 at the request of
 Washington State Department of Natural Resources

J. M. Olson Jr. & Davis, Dep.
 County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2),
 Chapter 50, Laws of 1973.

610" Survey of 1896
East on a tie line on provisional base ~ ~
40.00 Set a post.

15" Fir	N 6.5"E	30 L	19.80'
12" Fir	S 77"E	30 L	19.80'

1/4 corner	5.5	5.8	7.3N R8E
------------	-----	-----	----------

FOUNO. SICAMANIA CO. ENGINEERS

Pipe & BRASS CAP

18 "FIR STUMP" USE 19.9' TO FACE

W/VA INKERS ON BOTTOM OF FACE, CUT ON

below sub.B, "P" SEARCHED ON LOC Lying

Net to stump

15" FIR STUMP	ST77E	19.5	70	FACE-
---------------	-------	------	----	-------

NOT BELOW SCIENCE "HIS BY" SCIENCE ON LOG

YING HEAT TO STUMP

other recorded surveys using this corner position.

book / pg 118

book 2 pg 21

book 11 pg 261

book 1 pg 260

Corner is trav. sta. 160

60600m
BRASSLER

28-81-11

$$\begin{array}{r} 720.92 \\ \underline{695} \\ 25 \end{array}$$
