

LAND CORNER RECORD

T. 3 N. R. 8 East, W.M. Skamania County
 Segregated Surveys: Corner Code No. A-9
 Name: n/a Corner No.: n/a
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite

1. History of Corner Establishment and Subsequent Restoration:

Originally set by G.L.O. surveyor, Robert A. Webster, in 1896.
 No restoration found.

2. Description of Evidence Found:

33" Fir B.T. at N 58 W, 24.63 feet from corner position.
 37" Fir B.T. with visible scribe at N 53 E, 27.23 feet from corner position.
 45" Fir B.T. at S 50 E, 18.64 feet from corner position.
 35" Fir B.T. at S 41 W, 28.69 feet from corner position.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.22 Page No. 55 Date of work 12-2-82

Shown on D.N.R. Final Map #462. See corner diagram on reverse side.

On 12-2-82, the D.N.R. set a standard D.N.R. iron pipe with stamped brass cap at intersection of G.L.O. distances from Live B.T.'s (distance measured from B.T. faces).

Washington Plane Coordinates: South Zone Y 166,605.20 X 1,664,782.50
 3rd Order Accuracy. Derived From: 1975 Olson Eng. survey data at S.W.
 corner Sec. 5 (Recorded in Bk. 1 page 54, Records of Skamania County)
 Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept-29, 1983

Signature

11977

Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this 6th day of OCTOBER 1983 at 1:20 P.M. In Book 3/8 of MONUMENTS at page 64 at the request of Washington State Department of Natural Resources

M. Olson Dep. & News Rep
 County Auditor

