

LAND CORNER RECORD

Skamania County
T. 3 N. R. 8 East, W.M. Corner Code No. A-5
Segregated Surveys:
Name: n/a Corner No. n/a
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:
Originally set by G.L.O. surveyor, Robert A. Webster, in 1896.
No restoration found.

2. Description of Evidence Found:

18" Fir B.T. snag at N 82 W, 82.5 feet from corner position.
42" Fir B.T. at N 52 E, 9.73 feet from corner position.
19" Fir B.T. with visible scribe at S 69 E, 32.0 feet from corner position.
46" Fir B.T. at West 10.27 feet from corner position.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.22 Page No. 57 Date of work 11-18-82

Shown on D.N.R. Final Map #462. See corner diagram on reverse side.

On 11-18-82, the D.N.R. set a standard D.N.R. iron pipe with stamped brass cap at intersection of record distances from live B.T.'s (distances measured from B.T. faces).

Washington Plane Coordinates: South Zone Y 166,637.57 X 1,659,531.07
3rd Order Accuracy. Derived From: 1975 Olson Eng. survey data at S.W.
corner Sec. 5 (Recorded in Bk 1 page 54, Records of Skamania County)
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept. 29, 1983

Signature

11977
Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this 6th day of OCTOBER, 1983 at 1:40 P.M. In Book 3/8 of MONUMENTS at page 68 at the request of Washington State Department of Natural Resources

J.M. Olson by J. New, Sep
County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

