

96497

RES 20-1808(9-77)

BOOK 3/4 PAGE 9

LAND CORNER RECORD

Skamania Clark County
 T. 2 N, R. 4 East, W.M. Corner Code No. Z-25
 Segregated Surveys:
 Name: n/a Corner No.: n/a
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Originally set by Justin Chenoweth during 1856 G.L.O. survey of TIN. R4E.
 In May 1971, Dept. of Game noted 2 B.T's. and a stone mound, and set a 1-1/4" pipe and cap which was not found during D.N.R. survey.

2. Description of Evidence Found:

58" live Fir B.T. with visible scribing at N 72 W, 85.8 ft.
 18" diameter mound of rock at N 82 W, 20.4 ft.
 50" live Fir B.T. at S 63 W, 269 ft.
 50" live Fir B.T. at S ⁵⁴ 63 E, 98.34 ft.
 m-4-k.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 607.07 Page No. 36 Date of work 22 July, '81

Set standard D.N.R. iron pipe and stamped brass cap from intersection of 2 live Fir B.T's. (NW & SE B.T's.)
 Shown on D.N.R. Final Map 441.
 See sketch on back.

Washington Plane Coordinates: South Zone, Y 104,813.42 X 1,552,659.72
 3rd Order Accuracy. Derived From: USC & GS 'Ells' and DNR 3-3N-4E

Pin Pointed on Photo No. Date Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept. 27, 1983

M. A. Kinnaman 11977
 Signature Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this 6TH day of OCTOBER 1983 at 2:15 P.M. In Book 2/4 of MONUMENTS at page 9 at the request of
 Washington State Department of Natural Resources

J. M. Allen by J. Davis, dep.
 County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2) Chapter 50, Laws of 1973.

G.L.O. 1857

Post

4" Alder	N 7 E	84 LKS
10" Fir	N 78 W	130 130 LKS
6" Fir	S 58 E	149 LKS
6" Fir	S 63 W	408 LKS

Corner is trav. station 402 - pg 33 this book.

Township Cor

58" LIVE FIR BT 24/UNDEB SERVICE
7 SEVERED BRCH 1.30" INTO TAC
W22W 85 8 FT. 1.3" INTO TAC
500 LIVE FIR BT DID NOT CHOP INTO
554C 98.34 FT BT TAC
50" LIVE FIR 563W 269' BT TAC

Dept. of Game Survey, May, 1971, notes 2 BT's and pit of stone. They set 1 1/4" pipe/cap - we did not find pipe, but pile of stones are 20.4 feet off as shown on sketch.

