

96499

RES 20-1808(9-77)

BOOK 1/5 PAGE 19

## LAND CORNER RECORD

T. 1 N, R. 5 East, W.M. Skamania County  
 Segregated Surveys: Corner Code No. A-1  
 Name: n/a Corner No. n/a  
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

## 1. History of Corner Establishment and Subsequent Restoration:

Originally set by Justin Chenoweth during 1856 G.L.O. survey of TIN. R4E.  
 In May 1971, Dept of Game noted 2 B.T.'s. and a stone mound, and set a 1-1/4" pipe and cap which was not found during D.N.R. survey.

## 2. Description of Evidence Found:

58" live Fir B.T. with visible scribing at N 72 W, 85.8 ft.  
 18" diameter mound of rock at N 82 W, 20.4 ft.  
 50" live Fir B.T. at S 63 W, 269 ft.  
 50" live Fir B.T. at S 63 E, 98.34 ft.  
 54  
 M.A.K.

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location: Diagram corner and indicate meridian and reference to map of record: Surveyor's Field Book No. 607.07 Page No. 36 Date of work 22 July, '81

Set standard D.N.R. iron pipe and stamped brass cap from intersection of 2 live Fir B.T.'s (NW & SE B.T.'s.)  
 Shown on D.N.R. Final Map 441.  
 See sketch on back.

Washington Plane Coordinates: South Zone, Y 104,813.42 X 1,552,659.72  
 3rd Order Accuracy. Derived From: USC & GS 'Ells' and DNR 3-3N-4E

Pin Pointed on Photo No. Date Located at

## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept. 27, 1983

Signature

11977  
Certificate No.

## AUDITOR'S CERTIFICATE

Filed for record this 6th day of OCTOBER 1983 at 2:25 P.M. In Book 1/5 of MONUMENTS at page 19 at the request of Washington State Department of Natural Resources

J. M. Almon County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

