

RES 20-1808(9-77)
96787

STATE OF WASHINGTON
DEPARTMENT OF NATURAL RESOURCES
BUREAU OF SURVEYS AND MAPS

BOOK 4/7 PAGE 79

LAND CORNER RECORD

T. 4 N, R. 7 E, W.M. County SKAMANIA
Segregated Surveys: Corner Code No. Z-21
Name: N/A Corner No.: N/A
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: ORIGINALLY SET BY G.I.O. SURVEYOR, JACOB RICHARDSON, DURING 1895 G.I.O. SURVEY. IN 1903, G.I.O. SURVEYOR, ROBERT F. WHITHAM, SET THE CLOSING CORNER FOR 211, TEN-RTE, 3.14 CHAINS EAST OF THIS CORNER (HE DESTROYED MARKINGS SOUTH OF LINE)


2. Description of Evidence Found:

1 B.T. - REMAINS OF 36" FIR (W/AXE MARKS) AT S75°E-34.3 FT.
OLD FOREST SERVICE TAGS
OLD UNREADABLE TAG UNDER THE SLUFFED OFF BARK FROM THE S.E. B.T.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600-24 Page No. 56 Date of work 10-13-83

SHOWN ON D.N.R. F.M. # 477. SEE CORNER DIAGRAM ON REVERSE SIDE.

SET STD. D.N.R. CONCRETE MONUMENT W/STAMPED BRASS CAP AT G.I.O. BEARING & DIST. FROM ROTTED 36" FIR STUB.



Washington Plane Coordinates: SOUTH Zone, Y 166205.30, X 1642900.52
3RD Order Accuracy. Derived From: TIES TO USC & GS "GREENLEAF"
& USC & GS "SEDUM POINT"
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date December 1, 1983

Signature M. A. Kinnaman Certificate No. 11977



AUDITOR'S CERTIFICATE

Filed for record this 5 day of Dec 1983 at 1:40 P.M. In Book 4/7 of Monument at page 79 at the request of

Dept of Natural Resources

Larry M. Olson
County Auditor

96787

GLO Survey of 1895 (Jacob Richardson)
80.00' set post

10" Fir	N75E	52 kts	34.32'
36" Fir	S75E	52 kts	34.32'
8" Fir	S88W	75 kts	49.50'
8" Fir	N55W	54 kts	35.64'

In 1903, Robert Witham, surveying
T340 R7E, set a closing corner 3.14 ch east of
the corner and destroyed markings south of line
Std Sec. Coenue 3513L T4N R7E

Found Remains of 36" Fir
S75E 34.3 FT. AXE MARK
OLD FOREST SERVICE TMS
ON BLAZED FIRS, 22" Fir S70E
32' 24" Fir N75E 33.7 FT. (now)

Found very old unreadable log under
the shafted off bark from the SE BT.

