

97316

LAND CORNER RECORD

Skamania County
 T 4 N, R 8E W.M. Corner Code No. Y.73-1.38
 Segregated Surveys:
 Name: HES 193 Corner No.: 3
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite

1. History of Corner Establishment and Subsequent Restoration:

Corner set by U.S. Forest Service Surveyor K.P. Cecil under special instructions dated April 13, 1915 during April 1915:

Set Basalt stone 24"x10"x10" over stone marked with an X.

Marked:

20" Fir S25-47E-65 lks..

24" Fir S70-35E-127 lks..

2. Description of Evidence Found:

Basalt stone 24"x13"x12" marked 3 HES 193 on South.

Orig. 20" Fir now 32" sawed D-Fir stump S26E-65 lks. obvious healed face in top of stump.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 1 Page No. 7 Date of work 2/84

Set 2 1/2"x30" Aluminum pipe with a 2 1/2" Aluminum cap-buried orig. stone in hole next to monument.

New Bearing Trees:

13" D-Fir N24 1/2W-10.7 ft. scribed X3HES193BT and with a 3/4" Brass disk stamped PLS 16337.

16" D-Fir N70E-12.1 ft. scribed X3HES193BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard post S76W & S61E with decals 54-2 and survey marker.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.

Marked: No. 3
 HES 193
 1984
 PLS 16337

Washington Plane Coordinates: Zone, Y, X
 Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at:

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date MAR 12 1984

Signature

Certificate No. 16337

[SEAL]



AUDITOR'S CERTIFICATE

Filed for record this 23 day of Mar 1984 at 12:15 P.M. In Book 4/8 of Monument at page 7 at the request of

Gary M. Chase
 County Auditor

Form prescribed by B of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of