

97325

LAND CORNER RECORD

T. 3 N, R. 8E W.M. Skamania County
 Segregated Surveys: Corner Code No. E-1
 Name: Section corner: Corner No.: Section:
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Originally set by Deputy Robert E. Webster under contract No. 414 during Sept. 1896.
 Set wood post:

Marked:

6" Hemlock N77½E-15½ lks..

12" Hemlock S2E-40½ lks..

This corner has been accepted as perpetuated by other surveyors.

2. Description of Evidence Found:

½" pipe in rotted (4"x4")? post in mound of rocks.

3 DNR location tags.

Steel post 3 ft. West of pipe.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

1 Page No. 3 Date of work 2/84

Set 2½" x 30" Aluminum pipe with a 2½" Aluminum cap and buried pipe beside it.

New Bearing Trees:

12" D-Fir N48E-20.4 ft. scribed S6T3NR8EBT and with a ¾" Brass disk stamped PLS 16337.

9" D-Fir S18E-20.15 ft. scribed S7T3NR8EBT and with a ¾" Brass disk stamped PLS 16337.

Painted red band and blazed red on new BT's.

Set guard post 3 ft. South of monument with decal survey marker only.

Nailed 54-4 and 54-3 to all BT's.

Stamped: T3N R8E
 S6
 R7½E S7
 1984
 PLS 16337

Washington Plane Coordinates: Zone, Y, X
 Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date MAR. 13, 1984

Signature

Certificate No. 16337

AUDITOR'S CERTIFICATE

Filed for record this 23 day of Mar 1984 at 12:15 P.M. In Book 3/8 of Monuments at page 81 at the request of

County Auditor

