LAND CORNER RECORD
Skamania County
Corner Code No
Name: Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.
History of Corner Establishment and Subsequent Restoration:
Deputy Alonzo Gesher under contract No. 571 during June and July 1901
marked:
30" Red Fir 2 notches on North and South sides.
Description of Evidence Found:
Now 46" D-Fir with two notches on the North and South.
Describe Monument, Accessories, and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to man of record. Suppose Title Back No.
gram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 1 Page No. 9 Date of work April 1984
Set two 21/21 x 30" Aluminum pipes with 21/21" Aluminum caps. Marked: T4N R7/32
N45W-10:1 feet.
S45W-7.8 feet. Attached 54-4 sign to Line Tree.
PLS 16337
Washington Plane Coordinates: Zone, Y , X Order Accuracy. Derived From:
Pin Pointed on Photo No. Date Located at
SURVEYOR'S CERTIFICATE [SEAL]
This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 19, 1984
Signature Certificate No.
AUDITOR'S CERTIFICATE
Filed for record this 2.3 KD day of May 1934 at 2:10 P.M. In
Book 772 of Manufactures at page 24 at the request of
in Alvert 1 2 2

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.