

98169

10/6 PAGE 15



D. R. BUNTING & ASSOCIATES
ENGINEERS & SURVEYORS
P. O. Box 326 Phone 206-494-4555
Packwood, Wa. 98361

LAND CORNER RECORD

T 10 N. R. 6E W.M.

Segregated Surveys:

Name:

LEWIS Skamania County

Corner Code No. J-13

Cor for Secs. 9, 10, 15 & 16

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Set a granite stone, 24x16x8 ins., 18 ins. in the ground, for cor of secs. 9, 10, 15 & 16, marked with 4 notches on S. and 3 notches on E. edge; from which
Hemlock, 30 ins. dia., bears N. 67° E., 5 lks. dist., mkd. T 10 N R 6 E S 10 B T.
Hemlock, 36 ins. dia., bears S. 41° E., 33 lks. dist., mkd. T 10 N R 6 E S 15 B T.
Hemlock, 20 ins. dia., bears S. 71° W., 51 lks. dist., mkd. T 10 N R 6 E S 16 B T.
Hemlock, 30 ins. dia., bears N 28½° W., 79 lks. dist., mkd. T 10 N R 6 E S 9 B T.

2. Description of Evidence Found:

Stone approx. 8x16 ins., 6 ins. under Mt. St. Helens ash, with 4 notches in top edge and 3 notches in E edge, from which

Hemlock stump bears N28½°W, 51.76 ft. dist., mkd. "R 6 S" with other scribing overgrown.

Hemlock stump out of ground and leaning but stump hole located original position within a few feet, bears approx. N67°E, approx. 3 ft. dist., no markings remaining.

At a third bearing tree distance and bearing from the stone, a depression was found, probably the stump hole of bearing tree long ago rotted away.

At the fourth bearing tree distance and bearing, no evidence could be seen.

Corner's location had been verified by Forest Service before recent logging disturbance.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

Page No. Date of work

Left the stone undisturbed except uncovered and extending 3" above the ground, from which

An iron pipe, 2½" dia., 30" long, 24" in ground, with split and flared bottom end, bears S71°W, 35.03 ft. dist., mkd. REFERENCE MONUMENT S71W 35.03 FEET 11564.

An iron pipe, 2½" dia., 30" long, 24" in ground, with split and flared bottom end, bears N28½°W, 47.66 ft. dist., mkd. REFERENCE MONUMENT N28 30W 47.66 FEET 11564.

The stumps described above.

Note that bearings of two of the new pipe reference monuments are intentionally the same as bearings of two of the original bearing trees.

Bearing basis was magnetic needle with declination 22° east.

Washington Plane Coordinates: Zone, Y

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date June 29, 1984.

Signature

11564

Certificate No.

98169

AUDITOR'S CERTIFICATE

Filed for record this 10TH day of SEPTEMBER 1984 at 12:20 P.M. In Book 10/6 of MONUMENTS at page 13 at the request of

BUNTING & ASSOCIATES

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

