

LAND CORNER RECORD

Skamania

County

T 3 N, R 7 East, W.M.

Corner Code No. CD - 25

Segregated Surveys:

Name: Witness Point from 1903 resurvey

Corner No.: n/a

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Originally set as East 4 corner of Section 1, Township 3 North, Range 7 East, W.M., by G.L.O. surveyor, Jacob Richardson, during 1895 survey.

A 1901 G.L.O. (Gesner) resurvey found original 12" Fir Corner Tree.

In 1903, G.L.O. surveyor, Robert F. Whitham, found original tree post corner and remarked as Witness Point.

2. Description of Evidence Found:

1 B.T. stump at N.50 E., 13.0 ft.

Stump remains at corner position.


Stump remains at S.25 W., 17.0 ft.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.24 Page No. 54 Date of work 9-25-'84

Witness Point corner position is in center of proposed road R/W, so two D.N.R. aluminum monuments with caps were set as on line Reference Monuments.

Shown on D.N.R. Final Map # 315.

See corner diagram on reverse side.



Washington Plane Coordinates: South Zone, Y 163,487.88, X 1,648,085.33
3rd Order Accuracy. Derived From: Ties to USC & GS Control Stations
'Greenleaf' and 'Sedum Point'

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Jan 15, 1985

Signature

11977

Certificate No.

[SEAL]



AUDITOR'S CERTIFICATE

Filed for record this 21st day of JANUARY 1985 at 11:52 A.M. In Book 3/7 of MONUMENTS at page 58 at the request of Washington State Department of Natural Resources.

William W. New Dep
County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

5681 to 075

North 40.00 Intersect a fir 10" diam for $\frac{1}{4}$ cor.

40" fir 702 25052 20L

12" fir 525w 26L

1901 Resurvey of 2nd Guide Meridian

North 40, 07 2 fir 12" diam

40' fir 205N 202

14" fir, 525w 26L

1903 Retracement of E. boundary, S. 1, 3N 7E

North 39.52 $\frac{1}{4}$ bears E 35. Lints dist. cont.

Corner tree in good condition, BT's burned.

Marks old BT's as W.P.B.T. Marks corner
tree as W.P. This is an angle point on
the section line.

GLD Witness Point between S. 1, T3N R7E
and S. 1, T3N R7½E

Found / BT stamp at N50E, 13' 00 scribble.

Stump remains at corner position.

Stamp remains at S25W 17'

W.P. is in center of proposed road R/W.

Set RM 1 & 2 N & S of proposed R/W on the section line

