

99337
RES 20-1808(9-77)

STATE OF WASHINGTON
DEPARTMENT OF NATURAL RESOURCES
BUREAU OF SURVEYS AND MAPS

BOOK 37 PAGE 61

LAND CORNER RECORD

T. 3 N. R. 7 East, W.M. Skamania County
Segregated Surveys: Corner Code No. A - 25
Name: Supercedes L.C.R. filed under A.F. #98800 Corner No. n/a
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:
Originally set by G.L.O. surveyor, Jacob Richardson, during 1895 G.L.O. survey.
During 1903 G.L.O. retracement survey this corner was found and reestablished by Robert F. Whitham.
In 1978, the Department of Natural Resources set a D.N.R. concrete monument at calculated corner position.
In Sept. 1984, the Department of Natural Resources reset found D.N.R. concrete monument to newly calculated modified single proportion corner position. Date restamped '1984'.

2. Description of Evidence Found:
Above described D.N.R. concrete monument with stamped brass cap. Brass cap was restamped with date '1984'.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.12 Page No. 37 Date of work 9-26-'84

This superceded L.C.R. is to correct erroneous northing coordinate.
Corner shown on D.N.R. Final Map #315.
See corner diagram on reverse side.



Washington Plane Coordinates: South Zone Y 166,098.14 X 1,648,094.37
3rd Order Accuracy. Derived From: Ties to USC & GS Control Stations:
"Greenleaf" and "Sedum Point"
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date May 30, 1985
M. A. Kinnaman 11977
Signature Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this 5th day of JUNE 1985 at 11:55 AM. In Book 37 of MONUMENTS at page 61 at the request of Washington State Department of Natural Resources.

M. A. Kinnaman By: J. D. Davis, Dep
County Auditor Registered S

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973

North	80.00	Set fir post
-------	-------	--------------

10.00	Set fir post
-------	--------------

12" fir N48W 107L

6" fir 582.30'w 145 L

1901 Resurvey of 2nd Guide Meridian

North	78.31	found corner
-------	-------	--------------

1903 Retirement of 2nd Guide Meridian

North 79-61 corner bears E, 40 links distance.

Post & BT's burned down. Set a fire.

Post. raised mound of stone around

Post 30" base 20" high

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

10000 Ship Cover	36	742	W. M.
	1	75	
	36	75	

100

Found no original evidence

9.26.84

Gordon
Brosder

$$\begin{array}{r} 37 \\ \hline 600.12 \end{array}$$
