RECORD CORNER , W.M.; Skamania 7E (206) 256-8008 county JOHN G. LAWSON 14612-A 4th Plain-Rd. numbered Professional Land Surveyor Registered Professional Engineer Vancouver, WA 98662 Corner Code Number: Page 1 of Corner Name: Section corner, 25, 26, 35, 36.

DLC, HES Mining Clasim, Indian Allotment, Federal Reserve, Townsite 1. History of Corner Establishment and Subsequent Restoration; description of Evidence Found: This corner was established by U.S. Deputy Surveyor Jacob Richardson in July, 1895. It was found in May, 1916 by Frederick W. Rase during a survey he made in May, 1916. The corner had been destroyed by a rock slide but the Fir, 30" in diameter, Section 36 B.T. was found scribed and in good condition in 1916. We found a ± 28" diameter Fir snag without bark and gnarled fire scars. There was some fairly recent axe work on a scar ±4" above the ground. We sawed out scars, but found only pitch seams. No scribing or axe work was found. Original B.T. must have been bank scribed. G.L.O. bearing and distance from this snag places the corner within 2 feet of the location matching 1916 witness corner to the East. 2. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corper and indicate meridian and reference to map of record. LAWSON LAND SURVEYING Job # 34 -83 - 260407; Date of Work: November, 1983 This corner falls on side of a vertical rock cliff so we set a witness corner on the East side of Wind River canyon. Washington Plane Coordinates: Zone, Y Order of Accuracy. Derived from: Located at Date Pin Pointed on Photo No. SURVEYOR S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Certificate Number 11989 99393 AUDITOR'S CERTIFICATE _ day of ___TULLE__ , 19*6*5 at <u>+ 21 35</u> Filed for record this 17 M _ at the request of MINUMENTS at Page __ 95

County Auditor