

99913

WEYERHAEUSER COMPANY
LONGVIEW AREA

BOOK 4/5 PAGE 12

LAND CORNER RECORD

 $\frac{36}{1.6}$

SKAMANIA

County
Corner Code No. A-1

T 4 N. R 5 E. W.M.

Segregated Surveys:

Name

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: GLO Oct 20, 1897 CHARLES A. HOMAN US DEPUTY SURVEYOR. FOUND BY USFS APPROX 1939. THEY SET 3'x3' CEDAR POST AND 3/4" I.P. WE FOUND REMAINS OF 1897 BT'S. RESET 2 1/2" ALUMINUM PIPE WITH CAP AT POST POSITION.

2. Description of Evidence Found: 3'x3' CEDAR POST; 3/4" IRON PIPE

REMAINS 30" HEMLOCK S82W 22.4 NO MARKS
GLO 30" HEMLOCK S82W 34 RKS.

REMAINS 36" FIR S59E 35.6 POSSIBLE AXE MARKS
GLO 36" F S59E 54 RKS

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 1-85 Page No. 6 Date of work 7-26-83

☐ REFERENCE PLATE

☒ SA-A SIGN ON BACK

☒ 1/4"x2 1/4" GALVANIZED NAIL ON
CENTER SIDE OF TREE
CARBONITE POST 2' SOUTH



14' FIR
MARKED
CC TAN R 4 E S 1 BT

6' FIR
MARKED
CC TAN R 5 E S 6 BT

MAGNETIC

Washington Plane Coordinates: Zone, Y, X

Order Accuracy: Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 8-2-83

Signature

LS 16196
Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this 11th day of SEPTEMBER 1985 at 2:20 P.M. In Book 4/5 of MONUMENTS at page 12 at the request of

ARCHIE B. CARPENTER

Witnessed by J. M. O'Brien
County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.