

100467

BOOK 76

PAGE 62

HAMPSTUR CORPORATION
600 Colorado • P. O. Box 368
Kelso, WA 98626
(206-423-6100)

LAND CORNER RECORD

SKAMANIA

County

T 7 N R 6 E. W.M.

Corner Code No. Z-15

Segregated Surveys: 1/4 S. 34

Name: _____

Corner No.: _____

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally established by the G.L.O. in 1900, when a post was set for the corner and 2 B.T.'s were scribed. In 1921, Chester W. Pecore, re-ran the township line while performing a G.L.O. survey of T.6N.R.6E.. He found the original post and B.T.'s as set in 1900. He added an iron post with brass cap for the corner at that time. On Dec. 10, 1985, A. Gollersrud and R. Bogdon, of HAMPSTUR CORP., found the orig. brass cap and remains of both orig. B.T.'s and added a post and new tags as indicated and shown below, under the direction of C. Hampton, L.S., 18087.

2. Description of Evidence Found:

-a 3/4" galvanized iron pipe with 2 1/2" stamped brass cap, set in 1921, by the G.L.O., flush with the ground; (see diagram below).

-both original B.T.'s as indicated in the diagram below.

NOTE: Corner falls in small reprod. and no new B.T.'s were available to scribe at this time. This corner should again be re-referenced in approx. 20 years.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

PS-020 Page No. 46 Date of work 12/10/1985

LOCATION:

- in area of reprod.
- approx. S75°W--210 feet from a sharp curve in Plum Creeks spur 13 road,
- approx. 150 feet South of Plum Creek's spur 10 road which bears S80°W.


DRIVE A NEW 4 FT. STEEL FENCE POST WITH YELLOW LOCATION TAG FOR REFERENCE.

ORIG. BT WAS A 20" FIR IN 1900. NOW A 24" FIR STUMP, 12" HIGH, WITH HEAL-OVER AND SCAM AT 20" DIA. SHOWING ON TOP OF STUMP.

FOUND A 3/4" GALV. IRON PIPE WITH 2 1/2" BRASS CAP, SET FLUSH TO GROUND IN 1921 BY THE G.L.O.

NOTE: ADDED NEW B.T. TAGS TO BOTH ORIG. B.T.'s (NAMED TAGS ON TOP OF BT X STUMP TO NE)

ORIG. BT WAS A 12" FIR IN 1900 NOW AN 18" STUMP, 30" HIGH WITH VISIBLE SCRIBE "2" (FO. LONGER TAG WHICH READS N65°-48' E)



Washington Plane Coordinates: _____

Order Accuracy. Derived From: _____

Pin Pointed on Photo No. _____ Date _____ Located at _____

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date December 13, 1985

Signature *C. Hampton*

LS #18,087

Signature

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 20th day of Dec 1985 at 2:38 P.M. in Book 76 of Skamania at page 1 at the request of

*C. Hampton**Henry M. [Signature]*

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.