

T. N. TRANTOW SURVEYING

412 W. Jefferson P.O. Box 287

Bingen, Washington 98605 (509) 493-3111

LAND CORNER RECORD

T. 2 N, R. 5 E, W.M. SKAMANIA County Corner Code No. V-21

Name: Corner to Sections 25, 26, 35, 36 Corner No.:

DLC, IIES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: 2. Description of Evidence Found:

GLO in 1859 set this corner, from which bear:

15" D-fir, S28E, 342 links ((225.72 ft.) dead 50" D-fir, S61W, 150 links (99.00 ft.)
dead 30" D-fir, N3-3/4W, 170 links (112.20 ft.) dead 36" D-fir stub, N62E, 210 lks (138.60 ft.)BPA circa 1935 found this corner, and at station 536+20.41, calls "N 0°19'35" W
642.80 ft from the section corner identified by original bearing trees as the
corner common to sections 25, 26, 35 & 36..." (V.27, P.322 of Deeds)

Undated County records refer to a large chiseled stone, and fencepost at this corner.

DNR recovered this corner on 6/16/70 and set a concrete monument, from which bear:
20" fir, N84W, 49.67 ft 16" fir, N10E, 44.55 ft;
6" fir, S30E, 12.10 ft. All distances to spikes in trees.

2. Found concrete monument, and iron pipe previously used by C. Reynolds in survey
of Sec. 25. IP may have been established by BPA. S. 26 BT remains as a burned snag.
I accept the DNR monument and remeasured calls to tree centers.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record.

F.B. No. 20526 Page No. 14 Job No. 85247 Date of Work 24 October 1985

From the DNR monument, set 10" above the ground, bear:

30" D-fir snag, N4E, 112.2 ft. to center of snag. No visible scribing.



26" D-fir, N84W, 51.45 ft. to center of tree

24" D-fir, N10E, 45.6 ft. to center of tree

12" D-fir, S30E, 12.65 ft. to center of tree

All trees marked with aluminum witness tags.

I.P. bears N67E, 6.68 ft. from monument.

Washington Plane Coordinates: South Zone, Y 109623.24, X 1579059.35
third Order Accuracy. Derived From: 1970 land corner record & survey

Pin Pointed on Photo No. Symbol Located at.

SURVEYOR'S CERTIFICATE


This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
50, Laws of 1973.

Registered S

Signature

Date 24 October 1985

Certificate No. 15673



AUDITOR'S CERTIFICATE

Filed for record this 7th day of FEBRUARY 1986 at 4:35 P.M. In
Book 2/5 of MONUMENTS at page 35 at the request of

T. N. TRANTOW SURVEYING

J. Miller