

102274

BOOK 6/5 PAGE 11

State of Washington
DEPARTMENT OF NATURAL RESOURCES
BUREAU OF SURVEYS AND MAPS
LAND CORNER RECORD

22	23
27	26

Skamania County

T 6 N, R 5 E, W.M.

Corner Code No. R-17

Segregated Surveys:

Name: n/a

Corner Number: n/a

1. History of Corner Establishment and Subsequent Restoration:

Originally established in 1909 by GLO surveyor C. Frank Rhodes with a notched stone and 4 dead bearing trees.

No subsequent restoration found.

FILED FOR RECORD
SKAMANIA CO. WASH.
BY _____

2. Description of Evidence Found:

DEC 1 1 19 PM '86

GLO stone, firmly set, with proper notches.
26" fir stub at N25E 92 feet (hor.) with axe marks.
22" hemlock stub at S87E 21 feet (slope).
18" hemlock stub at S43W 17.5 feet (slope).
40" fir stub at N35W 8.6 feet (hor.)

AUDITOR
GARY M. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location.
Diagram corner and indicate meridian and reference to map of record. Surveyor's Field
Book No. 601.07, Page No. 55. Date of work June 10, 1986.

Corner is the original granite stone.

See reverse side for corner diagram.

SURVEYOR'S CERTIFICATE

[Seal]

This corner record correctly represents work
performed by me or under my direction in compliance
with the provisions of Chapter 50, Laws of 1973.
Date: November 19, 1986.

Signature

*H. Thomas Laird Jr.*21490
Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this _____ day of _____ 19____ at _____ M.
In Book _____ of _____ at page _____ at the request
of Washington State Department of Natural Resources.

Registered *S*
Indexed *S*
Filed *S*
Listed *S*

County Auditor

102274

BOOK 6/5 PAGE 11

State of Washington
DEPARTMENT OF NATURAL RESOURCES
BUREAU OF SURVEYS AND MAPS
LAND CORNER RECORD

22	23
27	26

Skamania County

T 6 N, R 5 E, W.M.

Corner Code No. R-17

Segregated Surveys:

Name: n/a

Corner Number: n/a

1. History of Corner Establishment and Subsequent Restoration:

Originally established in 1909 by GLO surveyor C. Frank Rhodes with a notched stone and 4 dead bearing trees.

No subsequent restoration found.

FILED FOR RECORD
SKAMANIA CO. WASH.
BY TOM LAIRD

2. Description of Evidence Found:

GLO stone, firmly set, with proper notches.
26" fir stub at N25E 92 feet (hor.) with axe marks.
22" hemlock stub at S87E 21 feet (slope).
18" hemlock stub at S43W 17.5 feet (slope).
40" fir stub at N35W 8.6 feet (hor.)

DEC 1 19 1986

AUDITOR
GARY M. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 601.07, Page No. 55. Date of work June 10, 1986.

Corner is the original granite stone.

See reverse side for corner diagram.

SURVEYOR'S CERTIFICATE

[Seal]

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973.
Date: November 19, 1986.

Signature

21490
Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this _____ day of _____ 19____ at _____ M.
In Book _____ of _____ at page _____ at the request
of Washington State Department of Natural Resources.

Registered ☒
Indexed ☒
Inspected ☒
Filed ☒
Listed ☒

County Auditor