

LAND CORNER RECORD

SKAMANIA

County
Corner Code No. 2-25

T 5 N, R 9 E, W.M.
Segregated Surveys:

Name: Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

CORNER ESTABLISHED BY DEPUTY SURVEYOR JACOB RICHARDSON UNDER
CONTRACT No. 303, OCTOBER 1892. SET POST FROM WHICH BEARS:
10" FIR N 58° E, 83 lks, SCRIBED "T 5N R 10E S 31 BT"
10" FIR N 9° W, 58 lks, SCRIBED "T 5N R 9E S 36 BT"
5" FIR S 64° E, 4 lks, SCRIBED "S C T 5N R 9 1/2 10E BT"

2. Description of Evidence Found:

10" OF, NOW 30", N 58° E, 54.78' WITH HEALED BLAZE
10" OF, NOW 36", N 9° W, 38.28', WITH HEALED BLAZE
FILED FOR RECORD
SKAMANIA CO. WASH
BY TERRA SURVEYING

OCT 28 9 54 AM '87

J. Pub, Dep.
AUDITOR
RAYMOND OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.


4 Page No. 12 Date of work 3-31-87

SET STD. 2 1/2" x 30" ALUMINUM PIPE AND CAP, 24" IN THE GROUND
IN A 2' x 2' x 6" MOUND OF STONE, FROM WHICH BEARS:

34" OF N 24° 45' W, 36.90 FT, SCRIBED "S 36 BT"

29" OF S 72° 45' E, 62.50 FT, SCRIBED "S 1 BT"

TREES HAVE RED PAINTED BANDS, TAGS AND BRASS
WASHERS, "PLS 18731" SET CARSONITE GUARD POST NEAR MONUMENT.



Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
50, Laws of 1973. Date 8/87

Signature

Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of.

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section
Chapter 50, Laws of 1973.

Registered S
Indexed, Jir
Filed
Mailed