

LAND CORNER RECORD

SKAMANIA

County

Corner Code No. 6-13

T 4 N, R 9E, W.M.

Segregated Surveys:

Name:

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

CORNER ESTABLISHED BY DEPUTY SURVEYOR JACOB RICHARDSON
UNDER CONTRACT No. 303, OCTOBER/NOVEMBER 1892. SET POST FROM
WHICH BEARS:
18" FIR, N 50° W, 81 Ks., SCRIBED "1/4 SBT"
12" FIR, S 55° E, 71 Ks., " " "1/4 SBT"

2. Description of Evidence Found:

NO REMAINS OF G.L.O. EVIDENCE FOUND.

FILED FOR RECORD
BY TERRA SURVEYING

OCT 28 10 19 AM '87


J. J. J. Dep.
AUDITOR
GARY M. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

4 Page No. 28 Date of work 7-28-87

SET STANDARD 2 1/2" x 30" FOREST SERVICE
ALUMINUM MONUMENT 18" IN THE GROUND, IN
A 36" x 24" x 12" MOUND OF ROCK, FROM WHICH BEARS:
17" D. FIR, S 75° 45' W, 25.8 FT., SCRIBED "59 1/4 BT"
14" D. FIR, S 10° 30' W, 24.1 FT., " " "59 1/4 BT"
(BEST TREES AVAILABLE)

TREES HAVE RED PAINTED BANDS, 54-36-54-9
SIGNS, AND BRASS "PLS 18731" WASHERS. SET CARSON ITC
GUARD POST NEAR MONUMENT.



Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
50, Laws of 1973. Date 8/87

Signature

Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of

County Auditor

Registered S

In 2

Book (2)

File 3

Mailed

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section
Chapter 50, Laws of 1973.