

LAND CORNER RECORD

T. 4 N, R. 7E, W.M. Skamania County
Segregated Surveys: Corner Code No. 2-5
Name: Section Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Robert F. Whitham in 1903 under Contract No. 600.

Set Hemlock post

10" Dogwood N23½E-60 lks.

40" Fir N60W-110 lks.

2. Description of Evidence Found:

Orig. 40" now 50" D-Fir snag N60W-72.6' obvious partially healed burned blaze with scribing.

Orig. NE BT gone.

Set monument at record bearing & distance from orig. BT.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 4 Date of work 6/87

Set 2½"x30" Alum. pipe with a 2½" Alum. cap 27" in ground stamped:

New Bearing Trees:

18" D-Fir N24W-22.5' scribed T4NR7ES31BT

20" D-Fir N32E-26.6' scribed T4NR7E32BT

R/R spike in base of 22" D-Fir S22E-9.83' to spike.

Both BT's have a 1" Brass disk stamped LS 16337.

Set guard posts E & W with decals 54-2 & survey marker.

Nailed 54-9 & BT signs to BT's & painted band & blazes red.

T4N R7E
S31 S32
T3N
1987
LS 16337

Washington Plane Coordinates: Zone, Y
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 9/22/87

Signature

16337
Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5(2), Chapter 50, Laws of 1973.

