

104578

State of Washington  
DEPARTMENT OF NATURAL RESOURCES  
BUREAU OF SURVEYS AND MAPS  
LAND CORNER RECORD

32 | 33

Skamania County

T 4 N, R 7 E, W.M.

Corner Code No. Z-9

Segregated Surveys:

Name: n/a

Corner Number: n/a

## 1. History of Corner Establishment and Subsequent Restoration:

Originally established in 1903 by GLO Surveyor Robert Witham with a post and two bearing trees.

Restored in 1969 by DNR employee John Lawson, with a 4"x4" DNR concrete monument, set record distance and bearing from the fir bearing tree.

## 2. Description of Evidence Found:

4"x4" DNR concrete monument

45" dead fir bearing tree at N5SW 7.35 feet to nail.

FILED FOR RECORD  
SKAMANIA CO. WASH  
BY D.N.R.

JAN 19 11 50 AM '88  
D. N. R. Dep.  
AUDITOR  
GARY E. OLSON

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.27, Page No. 46. Date of work April 14, 1987.

See corner diagram on reverse side.

Washington Plane Coordinates: South Zone, Y 166,508.53, X 1,627,173.95 Third Order Accuracy.

Derived from: NGS "MOWICH," NGS "SEDUM," DNR 1,4N7E, DNR 11,3N7E.

Pin Pointed on Photo No. \_\_\_\_\_, Date \_\_\_\_\_, Located at \_\_\_\_\_.


## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973.  
Date: January 6, 1988.

Signature H. Thomas Laird Jr. Certificate No. 21490

[Seal]

Registered S  
Indexed, Dir S  
Indirect S  
Filed S



## AUDITOR'S CERTIFICATE

Filed for record this \_\_\_\_\_ day of \_\_\_\_\_ 19 \_\_\_\_\_ at \_\_\_\_\_ M.  
In Book \_\_\_\_\_ of \_\_\_\_\_ at page \_\_\_\_\_ at the request  
of Washington State Department of Natural Resources.

County Auditor

'610 Survey of 1903.  
 EAST ON TRUE LINE ON S. Body Sec. 32  
 T4N R7E  
 80.00 CH. SET Maple Post from which  
 2" Dogwood N76°30'E, 68 L.  
 30" FIR N55°30'W, 11 L.

5-14-87

Laird  
Brossler  
Hanlin

600.27

46



STD SEC. CORNER 32|33 T4N R7E

4x4 CONC. MON. W/BASS CAP SET  
 by LAWSON, 1969

15" DEAD FIR @ N55 W 235 ft  
 (to RP NAIL)  
 B.T.

BT  
 15"  
 DEAD FIR

N55W  
71.34



S5E  
 24.40

40'

29" FIR STUMP

S2E  
 43.30

52" FIR STUMP

D.N.R. 4x4" CONC. MON. W/BASS CAP  
 8" ABOVE GROUND

BOOK 4/7 PAGE 114