

LAND CORNER RECORD

T. S. N. R. 9E, W.M.
Segregated Surveys:

SKAMANIA

County
Corner Code No. 2-23

Name:

Corner No.:
D.L.C., H.S., Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

CORNER ESTABLISHED by DEPUTY Surveyor JACOB RICHARDSON UNDER CONTRACT NO 383 OCTOBER / NOVEMBER 1892. SET POST FROM WHICH BEARS:
16" FIR, N47-30 W, 41 LKS "SC 1/4 SBT
18" FIR, S22E, 34 LKS "SC 1/4 SBT.

2. Description of Evidence Found:

NO REMAINS OF OLD EVIDENCE FOUND.

FILED FOR RECORD
SKAMANIA, WASH.
BY TERRA SURVIVOR

APR 14 12 17 PM '88

AUDITOR


GARY H. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 10 Page No. 8 Date of work 7-87

SET STANDARD FENCE SERVICE
2 1/2" x 30" ALUMINUM PIPE / CAP 24"
IN THE GROUND, FROM WHICH BEARS:
5/8" x 30" IRON ROD, N64-45E, 13.1 ft.
5/8" x 30" IRON ROD, S44-30W, 20.1 ft.

IRON RODS HAVE PLASTIC
"TERRA PLS 18731"

SET CEMENT GUARD POST NEAR
MONUMENT WITH APPROPRIATE SIGNS.
CORNER FALLS IN A CLEAR CUT.



Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date APR 12, 1988

Signature

Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5(2), Chapter 50, Laws of 1973.