

T. N. TRANTOW SURVEYING

412 W. Jefferson P.O. Box 287

Bingen, Washington 98605 (509) 493-3111

LAND CORNER RECORD

T. 3 N, R. 9 E, W.M. SKAMANIA County Corner Code No. 6-17

Name: $\frac{1}{4}$ corner to Sections 10 & 11 Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: 2. Description of Evidence Found:

GLO set corner in 1880, from which bear:

4" maple, N20E, 9.90 feet

15" fir, S25W, 17.82 feet

L.B. Smith (LS 5125) in 1956 did not recover corner, and used established fence corner for the position of this $\frac{1}{4}$ corner. No remains of original BT's were found.

Accepted fencepost for corner position, and set a 5/8x30" iron rod with plastic cap for this corner, at the NW corner of a south and east fenceline.

FILED FOR RECORD
SKAMANIA CO. WASH
BY T. N. TRANTOW SURVEYING

JUN 9 3 00 PM '88

AUDITOR

GARY H. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location, Diagram corner and indicate meridian and reference to map of record.

F.B. No. 30910 Page No. 14 Job No. 88388 Date of Work March 30, 1988

From the iron rod bear the following:

18" D-fir, N58E, 7.80 feet to nail @ center

18" D-fir, N52W, 9.14 feet to nail @ center

20" D-fir, S31W, 24.17 feet to nail @ center

All trees marked with aluminum witness tags

Washington Plane Coordinates: South Zone, Y NA, X
third Order Accuracy. Derived From:

Pin Pointed on Photo No. NA Symbol Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973.

Signature

Date 12 May 1988

Certificate No. 15673

AUDITOR'S CERTIFICATE

Filed for record this day of 19 at the request of

Book of at page

T. N. TRANTOW SURVEYING

County Auditor

McIntosh
Ind. 1/1
1/1
1/1
1/1