

T. N. TRANTOW SURVEYING

412 W. Jefferson P.O. Box 287

Bingen, Washington 98605 (509) 493-3111

LAND CORNER RECORD

T. 3 N. R. 9 E. , W.M. SKAMANIA County Corner Code No. J-13

Name: Corner to Sections 9, 10, 15 & 16

Corner No.:

DLC, HFS, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: 2. Description of Evidence Found:
GLO in 1880 set a post for this corner, from which bear:

12" RC, N45E, 11.88 feet

12" fir, N18W, 11.22 feet

5" RC, S38W, 9.24 feet

50" fir, S43E, 13.86 feet

L.B. Smith (LS 5125) in 1956 found 3 BT stumps, and apparently an iron pipe (plat indicated 'iron'), from which bear:

6" fir, N58E, 4.9 feet

3" fir, N32W, 2.7 feet (found)

8" fir, S20E, 12.2 feet

4" fir, S14W, 9.2 feet. (found)

Accepted iron pipe and marked new witnesses with aluminum tags.

FILED FOR RECORD
SKAMANIA CO. WASH
BY T. N. TRANTOW SURVEYING

JUN 9 3 02 PM '88

AUDITOR
GARY H. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record.

F.B. No. 30910 Page No. 24 Job No. 88388 Date of Work April 4, 1988

From the 3/4" iron pipe bear the following:

14" D-fir, S14E, 12.75 ft. to nail @ center of tree with healed face

6" D-fir, S16W, 9.40 ft. to nail @ center of tree with healed face

4" D-fir, N45W, 2.59 ft. to nail @ center of tree with healed face

14" D-fir, N65E, 5.15 ft. to nail @ center of tree.

Washington Plane Coordinates: South Zone, Y NA, X
third Order Accuracy. Derived From:

Pin Pointed on Photo No. NA Symbol Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973.

Signature

T. N. Trantow

Date 12 May 1988

Certificate No. 15673

AUDITOR'S CERTIFICATE

Filed for record this day of at page at the request of

T. N. TRANTOW SURVEYING

County Auditor