

T. N. TRANTOW SURVEYING

412 W. Jefferson P.O. Box 287

Bingen, Washington 98605 (509) 493-3111

LAND CORNER RECORD

T 3 N, R 9 E, W.M. SKAMANIA County Corner Code No. E-17

Name: Corner to Sections 2, 3, 10 & 11 Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: 2. Description of Evidence Found:

GLO in 1880 set a post for this corner, from which bear:

10" fir, S45E, 11.88 feet; 9" RC, S70W, 8.58 feet;

12" fir, N30E, 9.90 feet; 5" fir, N40W, 12.54 feet

L.B. Smith (LS 5125) recovered this corner in 1956, and set a 3/4x30" iron pipe:

8" fir, N31E, 8.3 ft, scribed S2BT

10" fir, N14W, 7.6 ft, scribed S3BT

16" fir, S06W, 17.5 ft, scribed S10BT

14" fir, S84E, 25.7 ft, scribed S11BT

Smith does not call the 3 BTstumps indicated as found on his plat.

2. No original BT's found, but located iron pipe as called, and three of Smith's witnesses, all with healed faces.

FILED FOR RECORD
SKAMANIA CO. WASH
BY T. N. TRANTOW SURVEYING

JUN 9 3 08 PM '88

AUDITOR
GARY L. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record.

F.B. No. 30910 Page No. 46 Job No. 88388 Date of Work April 12, 1988

From the iron pipe bear:

18" D-fir, N10W, 7.80 ft. to nail @ center

24" D-fir, S12W, 18.15 ft. to nail @ center

24" D-fir, S81E, 26.12 ft. to nail @ center

All trees marked with aluminum witness tags

Washington Plane Coordinates: South Zone, Y, NA, X
third Order Accuracy. Derived From:

Pin Pointed on Photo No. NA Symbol Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973.

Signature

Certificate No. 15673

Date 12 May 1988

AUDITOR'S CERTIFICATE

Filed for record this day of 19 at the request of
Book of at page M. In

T. N. TRANTOW SURVEYING

County Auditor