



106179

BOOK 6/6 PAGE 38

## LAND CORNER RECORD

HAMPSTUR CORPORATION  
1010 Douglas AS  
LONGVIEW, WASHINGTON 98632T 6 NR 6 E.        W.M. SKAMANIA County  
Segregated Surveys: 1/4 corner S. 8  
Name:        S. 17 Corner No.:         
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

## 1. History of Corner Establishment and Subsequent Restoration:

This corner was originally established in 1921 by Chester W. Pecore, under GLO contract, group #19, which consisted of an iron pipe w/brass cap and 2 scribed BT's. In 1977, Hagedorn, Inc. found the corner and referenced it to 3 trees, as indicated on their survey map recorded in BOOK 1 of SURVEYS at PAGE 142, in Skamania County. In 1981, Hobbs & Assoc.'s located the corner and referenced it with 2 scribed trees, as indicated on their LCR, filed in BOOK 6/6 at PAGE 4, with Skamania County. Then on July 29, 1988, HAMPSTUR CORP. maintained the corner as shown below, while working on a corner restoration project for PLUM CREEK TIMBER CO., under the direction of C. Hampton, L.S. #18,087.

## 2. Description of Evidence Found:

ORIGINAL GLO MONUMENT: (1"x36" iron pipe w/brass cap, 28" in ground); fd. as described.

## ORIGINAL 1921 BT'S:

- (20" Fir, N45°W--9 lks.); fd. badly decomposed stub, buried in dirt slide, at rec. loc.
- (12" Fir, S28°W--30 lks.); fd. badly decayed stub, 1 ft. high, at record location.

## 1981 RESTORATION BY HOBBS:

found both references as mentioned above and shown in the diagram below.

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

PS-056 Page No. 14 Date of work 7-29-1988

## LOCATION:

- on a 100% Northeast slope.
- 50 ft. South of a draw which bears Northeast.
- approx. 225 ft. West of a small creek which runs Northeast.
- approx. 600 ft. East of the end of a spur road on a North-South ridge.
- on an East-West cutting line, (clearcut to the North and timber to the South).
- found a USFS posted line running to the East and to the West.

1981 RP  
FD. 13" HEMLOCK  
W/VIS. SCRIBE  
S. 54.3/54.9 S. 16.1  
- ADDED R-R SPIKE TO  
CENTER OF NEW  
P.C. LOC. TAG.

WEST  
3.0'  
SET 5 1/2 FT.  
STEEL SPIKE  
POST W/LOC. TAG



FD. 610 1"x36" IRON  
PIPE W/BRASS CAP  
AS SET IN 1921

1981 RP  
FD. 29" FIR W/VIS.  
SCRIBE S. 54.3/54.9 S. 16.1  
- ADDED R-R SPIKE TO  
CENTER OF NEW LOC. TAG

Washington Plane Coordinates:        Zone, Y         
Order Accuracy. Derived From:       Pin Pointed on Photo No.        Date        Located at       

## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date October 19, 1988

Signature

Calvin J. Hampton

LS. #18,087

Certificate No



## AUDITOR'S CERTIFICATE

Filed for record this 13 day of October 1988 at        M. In  
Book 6/6 of        at page        at the request of       

County Auditor

Registered S  
Indexed S

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.