106496

Surveys Page 5

Book 3

FILED FOR RECORD
SKAMANIA COUNTY, WASH
BY USDA
JAN 30 12 43 PM '89
Auditor
CARL ... N

RECORD OF SURVEY
FOR
GIFFORD PINCHOT NATIONAL FOREST
LAVA THIN CADASTRAL SURVEY
53-05K3-8-05955J

NW COR. S.22

G.L.O.
COR - SET POST
BT - 36" CEDAR N54°E 39 LKS.
BT - 12" FIR 32°E 57 "
BT - 8" " 342°W 33 "
BT - 5" CEDAR N70°W 26 "
FOUND
COR - 2½" ALUM MON., MARKED
BT - 36" CEDAR STUMP N54°E 25.7'
BT - ROTTEN FIR STUMP 32°E 37.6'
BT - " " " 342°W 21.7'
BT - 13" CEDAR N70°W 17.1'
1984 BT - 8" HEM. N42°E 14.8'
1984 BT - 22" CEDAR S76°E 33.7'
SET - 6' ORANGE PLASTIC POST 4' S. OF CORNER.
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
" " SURVEYS BOOK 2 PAGE 34-160
HELD FOR CORNER

T4N R9E S15 1/4 S22 1984 PLS 16337

N1/4 COR. S.22

G.L.O.
COR. - SET POST
BT. - 6" FIR S52°E 15 LKS.
BT. - 10" " N27°E 22 "
FOUND
COR. - 1¼" I.P. W/2½" BRASS CAP MARKED
BT - STAKE W/RIBBON FOR POSITION S35°E 6.45'
R.P. - 7" COTTONWOOD S66°W 28.13'
R.P. - 22" CEDAR STUMP S30°E 19.18'
R.P. - ALUM. PIPE & CAP. (PROP. N1/4) N1°W 46.37'
SET - 54-9 SIGNS ON BACK OF R.P.S
- 6' ORANGE PLASTIC POST 4'E OF CORNER
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
HELD FOR CORNER

T4N R9E S15 1/4 S22 1987 PLS 16337

Fd. 2½" ALUM. PIPE w/ ALUM. CAP SET BY L. BISHOP IN 1984, MARKED T4N R9E S15 1/4 S22 1984 PLS 16337

Fd. TWO N1/4 CORNERS, ONE SINGLE PROPORTIONED AND ONE REPLACED OLD PIPE WITH EVIDENCE DATING BACK TO ABOUT 1946. I USED POSITION OF OLD PIPE AS THE N1/4 CORNER BASED ON THE OLD EVIDENCE.

U.S.F.S.

BROUGHTON LBR. CO
NW 1/4

NE 1/4

(G.L.O. N0°03'W 2640.00')
N0°46'36"E 2649.84'

2596.07'
[2596.84']

Fd. 1¼" I.P. w/2½" BRASS CAP (illegible) AND TREE MARKED C1/16 N3°09'35"E 199.11' OF CALCULATED POSITION FOR C1/4 CORNER.

C-E 1/16 COR. S.22

FOUND
COR - 1¼" I.P. w/2½" BRASS CAP MARKED
R.P. - 12" MAPLE S18°E 18.70'
R.P. - 6" CEDAR STUMP N48°W 30.89'
R.P. - ¾" I.P. N60°E 4.20'
SET - 54-9 SIGN ON BACK R.P.S
- 6' ORANGE PLASTIC POSTS 4'W, 4'7" S OF COR.
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
HELD FOR CORNER

SURVEYING C-E 1/16 S22 1987

WILLIAM G. FISHER

[2636.82']
2637.32'

[2640.53']
2640.50

S 89° 34'30" E 5277.82'
[S 89° 34'41" E 5277.36']

1320.25'
[1320.27']

1320.25'
[1320.26']

E 1/4 COR. S.22

G.L.O.
COR. SET POST
BT. - 6" HEM. N15°W 9 LKS.
BT. - 6" FIR N21°30'E 16 LKS.
FOUND
COR. - D.N.R. CONC. MON. MARKED
R.P. - 20" D. FIR S67°E 3.51'
R.P. - 24" " N30°W 33.57'
R.P. - 8" PINE N76°E 33.21'
SET - 54-9 SIGN ON BACK OF R.P.S
- 6' ORANGE PLASTIC POST 4' N. OF COR.
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
HELD FOR CORNER

T4N 1/4 S22 S23 R9E 1977

W1/4 COR. S.22

G.L.O.
COR. - SET POST
BT. - 5" WILLOW S46°E 9 LKS.
BT. - 9" FIR S76°W 11 "
FOUND
COR. - ¾" I.P.
BT. - 28" D. FIR S74°W 8.13'
BT. - 6" ROTTEN STUB S32°E 5.55'
R.P. - 36" D. FIR S22°E 19.87'
R.P. - 36" D. FIR N32°W 9.57'
SET - 54-9 SIGN ON BACK OF R.P. TREES
- 6' ORANGE PLASTIC POSTS 4'N & 4'W OF COR.
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
HELD FOR CORNER

U.S.F.S.
SW 1/4

BROUGHTON LBR. CO.

(2623.90')
2624.45'

WHITE SALMON RIVER

U.S.F.S.
W1/2 SE 1/4

E 1/2 SE 1/4

N0°51'52"E 5208.83'
5208.88'

N0°51'16"E 2612.82'
[2611.99']

[N0°50'42"E]
N0°49'58"E

S1/4 COR. S.22

G.L.O.
COR. - SET POST
BT. - 9" WILLOW S30°W 10 LKS
BT. - 5" CHERRY N15°E 6 "
FOUND
COR. - 1¼" I.P. W/2½" BRASS CAP, MARKED
R.P. - 6" D. FIR STUMP NORTH 25.80'
R.P. - 20" D. FIR STUMP S32°E 19.75'
R.P. - 18" D. FIR STUMP S66°W 29.50'
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
HELD FOR CORNER

SURVEYING S1/4 COR. S22 S27 1987

E 1/16 COR. S22/S27

FOUND
COR. - 1¼" I.P. w/2½" BRASS CAP MARKED
R.P. - 24" D. FIR STUMP N36°W 9.55'
R.P. - 24" D. FIR STUMP S85°E 8.95'
R.P. - 2" I.P. N23°E 3.1'
SET - 54-9 SIGN ON BACK OF R.P. STUMPS
- 6' ORANGE PLASTIC POSTS 4'N & 4'E OF CORNER
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
HELD FOR CORNER

SURVEYING E 1/16 S22 S27 1987

[1321.11]
1321.20'

1321.20' [1321.11']

N89°04'59"W 2642.40'
(G.L.O. N89°42'W 2636.70')
[S89°04'59"E 2642.22']
U.S.F.S.

SE COR. S.22

G.L.O.
COR - SET POST
BT. - 48" FIR N42°E 75 LKS.
BT. - 60" " S79°E 22 "
BT. - 36" " S38°W 14 "
BT. - 42" " N40°W 88 "
FOUND
COR. - D.N.R. CONC. MON., MARKED
BT. - 48" D. FIR STUMP N42°E 49.30'
BT. - 60" D. FIR SNAG S79°E 15.42'
BT. - 24" " STUMP S38°W 6.87'
R.P. - 44" " SNAG N4°E 14.59
SET - 54-9 SIGN ON BACK B.T.'s + R.P.s
- 6' ORANGE PLASTIC POST 3' W OF COR.
RECORDED IN SHORT PLATS BOOK 3 PAGE 128
HELD FOR CORNER

T4N R9E S22 S23 S27 + S26 1977

HISTORY OF SURVEYS

1. G.L.O. SURVEY BY JACOB RICHARDSON UNDER CONTRACT #383 IN 1892.
2. SOME RECORD OF DON STEVENSON, BROUGHTON LBR. CO. IN ABOUT 1946.
3. D.N.R. SURVEYED EAST LINE S.22 IN 1977.
4. LARRY BISHOP SURVEYED NORTH LINE S.22 IN 1984
5. TERRY TRANTOW SUBDIVIDED S.22 IN 1987.

LEGEND

- FOUND CORNERS
- SEC. LINES CALCULATED FROM SURVEY
- INTERIOR SEC. LINES CALCULATED FROM SURVEY
- PROPERTY LINES ESTABLISHED AND POSTED THIS SURVEY
- (G.L.O.) RECORD PER G.L.O. SURVEY IN 1892.
- [1321.11'] RECORD PER TRANTOW SURVEY FILED 12-28-87 IN BK. 3, PG. 128

NOTE

1. FIELD BOOKS: LAVA THIN No. 1, LAVA THIN No. 2, LAVA THIN No. 3
2. SURVEY METHOD: THEODOLITE & EDM

N

20°E MAG. VAR.

BASIS OF BEARING IS SOLAR OBSERVATION FROM POINT #4 ON OZO ROAD.

0 200 400 800 FEET
BAR SCALE:

EXAMINED AND ACCEPTED FOR THE U.S. FOREST SERVICE
THIS 4th DAY OF January, 1989
Donald Karsch
C.O.R.

I CERTIFY THAT THIS SURVEY WAS PREFORMED AT THE REQUEST OF THE GIFFORD PINCHOT NATIONAL FOREST

FOREST SUPERVISOR — DATE 1/4/89

FREDERICK L. MARTIN, STATE OF WASHINGTON, 10785, REGISTERED PROFESSIONAL LAND SURVEYOR

AUDITOR'S CERTIFICATE

Filed for record this 30th day of JAN, 1989 at 12:41 P.M. in book 3 of SURVEY at page 5 at the request of FRED MARTIN

County Auditor

SURVEYOR'S CERTIFICATE

This map correctly represents a survey made by me or under my direction in conformance with the requirements of the Survey Recording Act at the request of USDA FOREST SERVICE in AUG., 1988

Frederick L. Martin

Certificate No. 10785

SURVEY OF PART OF
SEC. 22,
T. 4 N., R. 9 E., W.M.

DWN BY	DATE	JOB NO.
E.L.A.	OCT. 1988	88-16
CHKD BY	SCALE	SHEET
F.L.M.	1" = 500'	1 OF 1

IVOR McCRAY'S INC.