



107758

BOOK 7/6 PAGE 72
HAMPSTUR CORPORATION
1010 Douglas A3
LONGVIEW, WASHINGTON 98632

LAND CORNER RECORD

T. 7 N.R. 6 E. W.M. SKAMANIA County
Segregated Surveys: Corner Code No. Z-7
Name: S. 1/4 corner of Section 32 Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally established in 1900, by Lewis Shelton, under GLO contract #552. The corner was then remonumented with a 1"x36" iron pipe with brass cap by Chester Pecore in 1921, while working under GLO contract, group #19. He added 2 additional BT's at that time. Then HAGEDORN, Inc. found the corner in 1977 and added additional references during a survey in Section 5. Then on July 29, 1988, R. Bogdon (from HAMPSTUR CORP.), located the above monument and added one additional RP and a steel reference post, as shown in the diagram below, while working on a "corner restoration" project for PLUM CREEK TIMBER CO., under the direction of C. Hampton, PLS #18,087.

2. Description of Evidence Found:

1900 ORIGINAL BT's:

-22" Fir, N54°E--37 1/2 lks.; found a dead stub at record location (was dead in 1921).
-24" Fir, S07°E--15 lks.; found a dead stub at record location (was dead in 1921).

1921 ORIGINAL GLO MONUMENT: found the 1"x36" iron pipe with brass cap, as described above and shown in the diagram below.

ORIGINAL 1921 BT's:

-10" Hemlock, N120°E--18 lks.; fd. a 23" live Hemlock (leaning), see diagram below.
-10" Cedar, S200°W--16 lks.; fd. a 23" live Cedar, with a partially vis. face, see below.


SUBSEQUENT RESTORATION:

fd. one RP. by HAGEDORN, Inc. as shown in the diagram below.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. PS-056 Page No. 29 Date of work 7-29-88

LOCATION:

- on a 25% Northwest slope.
- at the existing NE corner of approx. 8 yr. old reprod. (mature conifer to North and East).
- a USFS posted line runs South.
- a small creek which runs to the Northeast is located approx. 100 ft. North and approx. 100 ft. to the West.



Washington Plane Coordinates: Zone, Y
Order Accuracy. Derived From: X
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date August 28, 1989

Signature Calvin J. Hampton, PLS

LS #18,087
Certificate No



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

Registered
Indexed
Filed
Mailed