

JUN 27 1964
 P. Lawry

**CAL. FROM T.E.C.
TIES.**

CALC. CORNER USING
T.E.C. TIES.

588°-04'-20"E 2661.35' (IT APPEARS THAT 1919 SURVEY WENT 2640') IN THE 1919 SURVEY, HELD SET IN CONC. AS STATED AS THE CORNER OF 1919 C. 1/4.

1/4 CALC FROM TIES SHOWN IN
NEWELL GOSSET'S FIELD BOOKS
HIS ADJUSTED COORD. WERE ROTATED
FROM THE S.E. SECTION CORNER AND THE
THE N. 1/4 IT FIT WITHIN 0.5' OF HIS
CALC. POINT,
TT. MON. FROM CREEK TIES NOT
ACCEPTED. N47°-19'-46"W, 112.07'

FENCE TIES APPROX 500' SOUTH OF THE IRON PIPE FOUND IN 1919 VERY 5, 10' AS THEY MARK THE LINE. A FENCE TIE AT A STANDING FENCE POST 500' SOUTH IS WITHIN 1' OF LINE.

DETAIL OF 1919 SURVEY. THE PURPOSE
OF THIS SURVEY IS TO RETRACE THE LINES
ESTABLISHED BY THE 1919 SURVEY BY
G.E. LINN

DETAIL OF 19/9 SURVEY

SCALE 1"=200'

THE 1919 SURVEY WAS LOCATED BY HOLDING THE CALC. W. $1/4$ ACCORDING TO NWE. CO. AND THE IRON PIPE AS SHOWN ON THE 1919 SURVEY AS DUE EAST AND HELD THE 1919 ANGLES AS SHOWN ON HIS MAP.

THIS LINE APPEARS TO
FAR NORTH OF THE CREEK
APPROX. 100-140'

IT DOSE APPEAR THAT THIS
LINE WOULD BETTER FIT
THE IMPROVEMENTS ON THE
GROUND IF THE LINE WENT
FUTHER TO THE EAST.

LEGEND

- SET 5/8"X30" IRON ROD WITH 1-1/2 AL. CAP.
 SET 1-1/2"X30" IRON PIPE WITH 2-1/2" BRASS CAP.
 ■ FOUND MONUMENT OF RECORD
 +---+ FENCE LINES FROM TIES NEAR CORNERS.
 W.T. WITNESS TREES (SCRIBED) WITH NAIL APPROXIMATING THE CENTER.
 B.T. ORIGINAL GLO BEARING TREE
 () (GLO DISTANCE OR ANOTHER SURVEYOR'S DISTANCE OR DEED CALL)
 NWE. NORTHWESTERN ELECTRIC. CO.
 C. 1/4 M CENTER OF SECTION.
 C. CENTER LINE
 T.T. T. TRANTOW RLS. 15673

EQUIPMENT: 6" TOTAL STATION, CLOSED LOOP, CAL. JAN. 1989, CLOSURE
BY LEAST SQUARES, 1/309042, 0.038'±, 1/85998, 0.070'±.

AUDITOR'S CERTIFICATE
FILED FOR RECORDING THIS 22 DAY OF June, 1988.

AT 10:25 A.M., IN BOOK 3 OF SURVEYS PAGE 34 AT
THE REQUEST OF D2AB SURVEYING INC.,

THE REQUEST OF DEAN SURVEYING INC.
Jerry M. Olson by P. Lowmy
 COUNTY AUDITOR


D2AB SURVEYING INC
22 COTTONTAIL RIDGE ROAD
WHITE SALMON, WA. 98672
PHONE NO. 493 3376

REFERENCES:
G.L.O. NOTES, SURVEYS VOL. AND PAGE, T.E.C. SURVEY FOR PPL. IN 1973,
2/139, 2/135, PPL. SURVEY MAPS AROUND THE DAM SITE IN S. 2, S3,
AND NEWEL GOSSET FIELD NOTE LOCATED IN COUNTY, 6/58, 4/31,
7/10.

SURVEYOR'S CERTIFICATE
THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR UNDER
MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF THE SURVEY
RECORDING ACT AT THE REQUEST OF ORIE AND DELORES GARRETT IN DEC. 1989.

NOTES REGARDING THE IRON PIPE AT THE CENTER OF SECTION SHOWN ON THE 1919 SURVEY BY G.E. LINN.

1. IF THE IRON PIPE AT THE CENTER OF SECTION WAS SET BY LINN HE WOULD HAVE MEASURED FROM THE 1/4 CORNER WITH HIS RANDOM LINE AND THEN SET THE IRON PIPE BUT THE DRAWING INDICATES THAT THE LINE WAS RAN FROM THE IRON PIPE AT CENTER TO THE 1/4 CORNER.
2. ALSO IF THE IRON PIPE WAS SET BY HIM THE DRAWING WOULD HAVE SAID SO. THE LACK OF SUCH A COMMENT WOULD IMPLY THAT IT WAS IN EXISTANCE BEFORE THE SURVEY.
3. THE ONLY OTHER SURVEYOR WHO HAD DONE EXTENSIVE WORK IN THIS AREA WAS NEWEL GOSSET WHEN HE DID HIS WORK FOR N.W.E. CO. IN 1912. YET HIS WORK PLACES THE CENTER OF SECTION WEST OF THE IRON PIPE APPROX 138'-



Dennis R Peoples
DENNIS R. PEOPLES R.L.S. 25552
DATE 2/3/1990