## LAND CORNER RECORD

Skamania	County	
T 2 N, R E, W.M. Segregated Surveys:	Corner Code	No. E-11 S. 1/4 Sec. 4
Name:	. Corne	- No
DLC, HES, Tract, Mining Claim.	Indian Allolment, Federal Reserve	Townsile.
1. History of Corner Establishment and Subse G.L.O. survey in 1883 by Charles Sears Set post 3' long 3" square, 24" in the Silver Pine 40" diameter bears N. 65°30 Silver Pine 36" diameter bears S. 81° E	ground for 1/4 corner	FILED FOR RECORD SKANDA WASH BY TENNESON ENGINEER IN
		. Activity
2. Description of Evidence Found:		GARY M. OCSON
Found mound of stones Found 40" stump with tag marked S.70° W	., 35.0' (C.G.C. 10/30	Registered () Indexed, Dir () Indirect () Filmed Mailed
Describe Monument, Accessories and Corollar gram corner and indicate meridian and refer Page No. Date of work	y Data to Perpetuate the ence to map of record. S	is Corner Location. Dia- urveyor's Field Book No.
set R.P.'s as follows: Set P.K. in c	W., 57.5 ft. ir, N.58° W., 43.4 ft. enter of 48" stumo. N.	_
Washington Plane Coordinates: Zz Order Accuracy. Derived From:		
Pin Pointed on Photo No. Date.	Located at	
SURVEYOR'S CERTIFICATE		SEA OUD
This corner record correctly represents work punder my direction in compliance with the prosents of 1973. Date. State State of 1973. Date. State of 1973. AUDITOR'S CI	Ovisions of Chapter  ///30  Centrale No.	THO THAN SHOW AND SHO
Filed for record this le day of xelling.  Book of your xelling.	bkr	the request of
Filed for record this le day of xalling Book of your wan	Wary III Old	by P. Sowny deputy
Form prescribed by Bureau of Surveys and Maj Chapter 50, Laws of 1973.	os pursuant to the provi	sions of Section 5 (2),